

	X	
Sec.	9	

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____
Window Rock _____
Allottee _____
Lease No. 14-20-603-515

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	U. S. GEO. SURV. 60-10-10-10
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	EASTERN 10-10-10-10
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	X
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 29, 1960

Well No. 2 is located 330 ft. from N line and 2310 ft. from W line of sec. 9
NE/4 NE/4 NW/4 Sec 9 25N 19W N.P.P.N
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5993 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well plugged as Follows:

Set 30 sack reg. cement plug from 1300 ft. to 1546 ft.

Filled with mud from 425 ft. to 1300 ft.

Set 45 sack reg. cement plug from 200 ft. to 425 ft.

Filled with mud to surface pipe from 80 ft. to 200 ft.

Set 15 sack reg. cement plug from 0 ft. to 80 ft. and cemented 4 inch x 6 ft.

pipe marker in top of surface pipe.

Cleaned up location.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Drilling & Coring Exploration Co.

Address 1809 Laguna

Farmington, New Mexico

By Carl E. Harmon

Title Partner

Drilg. & Coring Expl. Co.



