Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

POR	M A	PPR	OVED	
Budget Be	T-COM	No.	1004-0	13
Expire	ı: Ma	erch	31, 1993	

Lease Designation and Serial No.

6. If Indian, Allottee or Tribe Name

SF	078155	
\sim		

Water Shut-Off Conversion to Injection

Dispose Water
(Note: Report results of an

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.

Use "APPLICATION F	OR PERMIT—" for such proposals	
SUBM	IT IN TRIPLICATE	7. If Unit or CA, Agreement Designation
I. Type of Well Oil Gas Duher P&A 2. Name of Operator Dugan Production Corp.		West Bisti Unit 8. Well Name and No. West Bisti Unit 165 9. API Well No.
3. Address and Telephone No. P.O. Box 420, Farmington,	NM 87499 (505) 325-1821	30-045-05524 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey) 660' FSL - 1980' FEL Sec. 1, T25N, R13W, NMPM	Description)	Bisti Lower Gallup 11. County or Parish, State San Juan, NM
12. CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE, R	EPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF AC	
Notice of Intent Subsequent Report APR 1	Abandonment Recompletion Plugging Back	Change of Plans New Construction Non-Routine Fracturing

Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent detes, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Casing Repair

Plugged well as follows:

1. Set cast iron bridge plug @ 4817'.

2. Spot 30 cu. ft. class "B" cement on top of bridge plug € 4817'. Gallup plug 4600' - 4817'.

3. Perforate 5½ casing @ 1992'. Spot 59 cu. ft. class "B" cement @ 2014. Displace cement to 1842'. Mesa Verde plug 1842' - 1992'.

4. Perforate 5½" casing @ 1254'. Spot 181 cu. ft. class "B" cement w/4% gel @ 1265'. Displace cement to 844'. Pictured Cliffs -Fruitland plug 844' - 1254'.

5. Perforate 5½ casing € 260′. Est. circulation through bradenhead to surface. Cement to surface with 118 cu. ft. class "B" cement w/4½ gel.

Job complete 4/4/95.

14. I hereby certify that the foregoing is true and correct			
Signed WALLEY JULY AND AND	Title	Operations Manager	Date4_5_95
(Thus space for Federal or State office use)			
Approved by Conditions of approval, if any:	Title		Date
···			APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false predictions of Teachiers statements or representations as to any matter within its jurisdiction.