


(SUBMIT IN TRIPLICATE)

Indian Agency Window Rock

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Survey 24-25-403-302
Allottee 24-25-403-302
Lease No. 24-25-70



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	Report of Re-perforating & Re-casing

RECEIVED

JUL 30 1958

FARMINGTON

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 28,

19 58

Well No. 2 is located 1000 ft. from S line and 1000 ft. from W line of sec. 4

NE 1/4 Sec. 4

(1/4 Sec. and Sec. No.)

25-E

(Twp.)

12-E

(Range)

N70W

(Meridian)

North Lower Gallup

(Field)

San Juan

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 6244 ft. N. E.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging, cementing points, and all other important proposed work)

TD PBTD
4792' to 4945' BOP - 5 1/2" OD casing set at 4940'. Perforated 5 1/2" casing from 4795' - 4798', 4824' - 4829' and 4894' - 4896' w/ 4 bullets per foot. Run retrievable bridge plug & set at 4892'. Run 2-3/8" NPH Tbg. & cement oil fraced above perforations with 50,000 gallons loose cement & 50,000 lb-40 sand down Tbg. & 5 1/2" Cas. Break down press. 2700#, avg. treating press. 2500#, Ann. press. 2500#. Finished w/ 200 bbl. lss. crude avg. inj. rate 12.3 BPM. Shutted well and retrieved bridge plug from 4892', leaving perforations from 4795' - 4798', 4824' - 4829', 4894' - 4896' and old perforations from 4900' to 4932' open. Shutted well & put well to pumping.

COMPLETION: Pumped 100 bbl. oil & water in 24 hours on 14-16" BPM. Gravity 28 corr. One Vol. 67,000 GPPD, 600 BOP.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Amoco Petroleum Corporation

Address Box 2 - Montfield, New Mexico

By R. F. Furse

Title Perman