

A 10x10 grid with a thick black border. The number '2' is located at row 1, column 4. The number '1' is located at row 4, column 5. All other cells are empty.

LOCATE WELL CORRECTLY

LOCATE WELL CORRECTLY

British-American Oil Prod. Co

Box 180, Denver 1, Colorado

Company

Address

Govt. Marye

Bisti Gallup

Field

New Mexico

State

3 1 25N 13W

Well No.

Sec. T. R.

Meridian

NMPM

County

San Juan

660

Location

ft. ~~EX~~ of N Line and 1980 ft. ~~EX~~ of W Line of NW/4

Elevation

6211 GL

(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Original Signed by:

Thomas M. Hogan

Signed

Date

July 13, 1956

Title

District Superintendent

The summary on this page is for the condition of the well at above date.

Commenced drilling March 27, 1956 Finished drilling April 13, 1956

**OIL OR GAS SANDS OR ZONES**  
(Denote gas by G)

(Denote gas by G)

|                                        |                            |
|----------------------------------------|----------------------------|
| No. 1, from <u>4856</u> to <u>4944</u> | No. 4, from _____ to _____ |
| No. 2, from _____ to _____             | No. 5, from _____ to _____ |
| No. 3, from _____ to _____             | No. 6, from _____ to _____ |

## IMPORTANT WATER SANDS

No. 1, from \_\_\_\_\_ to \_\_\_\_\_

No. 2 from \_\_\_\_\_ to \_\_\_\_\_

No. 3, from \_\_\_\_\_ to \_\_\_\_\_

No. 4, from \_\_\_\_\_ to \_\_\_\_\_

## CASING RECORD

| Size casing                                  | Weight per foot | Threads per inch | Make | Amount | Kind of shoe | Cut and pulled from | Perforated |     | Purpose |
|----------------------------------------------|-----------------|------------------|------|--------|--------------|---------------------|------------|-----|---------|
|                                              |                 |                  |      |        |              |                     | From—      | To— |         |
| 9-5/8"                                       | 32.3            | 10 rd            | H-40 | 209    | Baker        |                     |            |     |         |
| 5-1/2"                                       | 15.5            | 10 rd            | H-35 | 1939   | Baker        |                     |            |     |         |
| HISTORICAL RECORD OF THE WORKING OF THE MINE |                 |                  |      |        |              |                     |            |     |         |

## MUDDING AND CEMENTING RECORD

| Size casing | Where set | Number sacks of cement | Method used | Mud gravity | Amount of mud used |
|-------------|-----------|------------------------|-------------|-------------|--------------------|
| 9-5/8       | 220' KB   | 175                    | HQ MCC      |             |                    |
| 5-1/2       | 495' KB   | 100                    | HQ MCC      |             |                    |
|             |           |                        |             |             |                    |
|             |           |                        |             |             |                    |
|             |           |                        |             |             |                    |
|             |           |                        |             |             |                    |

## PLUGS AND ADAPTERS

|                       |        |           |
|-----------------------|--------|-----------|
| Heaving plug—Material | Length | Depth set |
| Adapters—Material     | Size   |           |

## SHOOTING RECORD

| Size | Shell used | Explosive used | Quantity | Date | Depth shot | Depth cleaned out |
|------|------------|----------------|----------|------|------------|-------------------|
|      |            |                |          |      |            |                   |
|      |            |                |          |      |            |                   |
|      |            |                |          |      |            |                   |
|      |            |                |          |      |            |                   |
|      |            |                |          |      |            |                   |

## TOOLS USED

Rotary tools were used from 0 feet to 4951 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet

Cable tools were used from 4898 feet to 4948 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet

## DATES

July 13, 1956 Put to producing May 15, 1956

The production for the first 24 hours was 379 barrels of fluid of which 97% was oil; -----% emulsion; 3% water; and -----% sediment. Gravity, °Bé. 37.5

If gas well, cu. ft. per 24 hours ..... Gallons gasoline per 1,000 cu. ft. of gas .....

Rock pressure, lbs. per sq. in. \_\_\_\_\_

## EMPLOYEES

\_\_\_\_\_  
Iron Drilling Company, Driller \_\_\_\_\_, Driller  
\_\_\_\_\_, Driller \_\_\_\_\_, Driller

## FORMATION RECORD

| FROM— | TO— | TOTAL FEET | FORMATION |
|-------|-----|------------|-----------|
|       |     |            |           |

FROM—
TO—
TOTAL FEET
(OVER)
FORMATION
10—43004-4

