

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.
New Mexico

Land Office
SF 030490

Lease No.

Unit

RECEIVED


SUNDRY NOTICES AND REPORTS ON WELLS

| | |
|---|---|
| NOTICE OF INTENTION TO DRILL..... | SUBSEQUENT REPORT OF WATER SHUT-OFF..... |
| NOTICE OF INTENTION TO CHANGE PLANS..... | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF..... | SUBSEQUENT REPORT OF ALTERING CASING..... |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE..... | SUBSEQUENT REPORT OF ABANDONMENT..... X |
| NOTICE OF INTENTION TO PULL OR ALTER CASING..... | SUPPLEMENTARY WELL HISTORY..... |
| NOTICE OF INTENTION TO ABANDON WELL..... | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 25, 1961

Federal "BU"
Well No. **1-3** is located **790** ft. from **N** line and **790** ft. from **E** line of sec. **3**
SERGE Sec. 3 **25N 10W N.M.P.M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat **San Juan**
(Field) (County or Subdivision)



The elevation of the derrick floor above sea level is **6796** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

August 7, 1961 - Ran 6750' of 4 1/2" , 10.5# J-55 Sals. casing, cemented with 235 sacks 50% Peamin with 6% gel and with 12# Gilsenite per sack. Tailed in with 100 sacks, regular neat mixed with Haladd #9 for fluid loss. Plug down @ 7:15 P.M.

August 9, 1961 - Ran tiein log and perforated Dakota Sand @ 6630-34', 6662-70 & 6690-6702' with 4 bullets per foot. River fraced with 55,000 gallons water and 40,000# of 20/40 sand.

August 12, 1961 - All frac water swabbed back - well making formation water and a vapor of gas.

August 18, 1961 - Squeezed perforations from 6662-70' and 6690-6702' with 500 gallons latex cement. Test perforations 6630-6634, made formation water. Squeeze perforations 6630-34' with 250 gallons latex cement.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **John H. Trigg**

Address **P. O. Box 520**
Roswell, New Mexico

By *John H. Trigg*
Title **Owner**



My dear Sir,

I have the honor to acknowledge the receipt of your letter of the 8th inst. in relation to the matter of the New York and New Jersey Electric Light and Power Company, and in reply to inform you that the same has been forwarded to the proper authorities for their consideration.

I am, Sir, very respectfully,
Yours truly,
J. M. Smith