GPO 9 18 507

Forn	1 <b>9-881</b> s
(Fe	b. 1961)
Γ	

		X

## (SUBMIT IN TRIPLICATE)

## UNITED STATES **DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY**

and Office	Senta Pe
.ease No	078124
T_44	undean

	AND REPORTS ON WELLS    SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	i i
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		I
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	·	1 1
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		X
NOTICE OF INTENTION TO PULL OR ALTER CASING		
NOTICE OF INTENTION TO ABANDON WELL.		
(INDICATE ABOVE BY CHECK MAR	K NATURE OF REPORT, NOTICE, OR OTHER DATA)	
	January 0,	<u>, 19.<b>5</b></u>
	• •	
Well No. 1-A is located 12 ft. from	$\mathbf{m}_{-}\left\{egin{array}{c}\mathbf{N}\\\mathbf{S}\end{array}\right\}$ line and i.e. $\mathbf{m}_{-}\left\{egin{array}{c}\mathbf{N}\\\mathbf{M}\end{array}\right\}$ line of sec.	<b>-</b>
(% Sec. and Sec. No.) (Twp.)		
₩ ildcet (Field)	(State or Territory)	<del></del>
The elevation of the derrick floor above sea l	evel is2718_ft.	
	AILS OF WORK	
		_
(State names of and expected depths to objective sands; show a ing points, and al	izes, weights, and lengths of proposed casings; indicate mudding jo l other important proposed work)	bs, cement-
1-4-5% This well was plugged and an	andoned in the following manner:	
1. 38 sks. reg. cement plug fro	om 5500' to 5600'.	
2. 38 aks. reg. coment plug fre		and the same of th
3. 38 aks. reg. cement plug fre	am 1950' to 2950'.	
4. 38 aks. reg. cement plug fr	1030' to 1130'.	1 (2 11)
		•
	JAN J	0 1958 N. COM.
o. Set surface pipe marker.	Ì ∩IL co	N COM
	100	T. 3
		''. 'S
	in writing by the Geological Survey before operations may be com	
Company 1 Paso Natural Cas Produ	CLE COMPERY	
Address P. C. Fox 15:5		
Parmington, New Assuice	By ORIGINAL SIGNED BY: JO	<u>SEPH E.</u> KREGI
	Title Petroleum bylneer	