

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office Santa Fe 078630

Unit Foster-Riddle

ENER

SUI	NDRY NOTICE	ES AND REPORTS ON WELLS
		SUBSEQUENT REPORT OF WATER SHUT-OFF.
OTICE OF INTENTION	TO DRILL	DEPORT OF SHOOTING OR ACIDIZING.
TICE OF INTENTION	TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING CASING
TICE OF INTENTION	TO TEST WATER SHUT-OFF	SUBSEQUENT OF PERPIT ING OR REPAIR.
TICE OF INTENTION	TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDIRECTION SUBSEQUENT REPORT OF ABANDONMENT
OTICE OF INTENTION	TO SHOOT OR ACIDIZE	SOBSEQUENT THE DICTORY
OTICE OF INTENTION	TO PULL OR ALTER CASING.	Subsequent Report of Sandfrac x
OTICE OF INTENTION	TO ABANDON WELL	pursequent nepot v
·	AND A POVE BY CHI	ECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	(INDICATE ABOVE BY	October 18th , 19_56
		ft. from S line and 1225 ft. from E line of sec. 13
ell No7	is located 1010	ft. from (S) line and the second (W)
	17 25N	N.M.P.M.
E/4 SE/4 S	ec. 13 25N	(Range) (Meridian) New Mexico
Ballard	1 100.) Tari	
	EAU.	(County or Subdivision) (State or Territory)
(Field)		
		1 1:-6504 ft
he elevation of	the derrick floor above	ve sea level is 6594 ft.
		DETAILS OF WORK
		DETAILS OF WORK
		ve sea level is 6594 ft. DETAILS OF WORK Index show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment nts, and all other important proposed work)
	Perforated 22 gas. Perfora Show of gas. per foot. Fl perforations sand, flushed	DETAILS OF WORK
State names of and ex	Perforated 22' gas. Perfora Show of gas. per foot. Fl perforations sand, flushed pressure 2650 rate 35.5 BPM MCF/day.	DETAILS OF WORK Index, show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coments, and all other important proposed work) 94-2302! with 4 holes per foot. No ted 2264-2274! with 4 holes per foot. Perforated 2238-2250! with 4 holes owing 372 MCF/day. Sandfraced through with 17,700 gallons water and 30,000# if with 2,300 gallons water. Breakdown of, treating pressure 1050#, injection of, After treatment flowing 7,460 ive approval in writing by the Geological Survey before operations may be commenced.
3 tate names of and expenses of another ex	Perforated 22' gas. Perfora Show of gas. per foot. Fl perforations sand, flushed pressure 2650 rate 35.5 BPM MCF/day.	DETAILS OF WORK Index show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coments, and all other important proposed work) 94-2302' with 4 holes per foot. No ted 2264-2274' with 4 holes per foot. Perforated 2238-2250' with 4 holes owing 372 MCF/day. Sandfraced through with 17,700 gallons water and 30,000# if with 2,300 gallons water. Breakdown off, treating pressure 1050#, injection off, treating pressure flowing 7,460 ive approval in writing by the Geological Survey before operations may be commenced. EER DRILLING CORP.
1 understand the Company BEI Address 40	Perforated 22' gas. Perfora Show of gas. per foot. Fl perforations sand, flushed pressure 2650 rate 35.5 BPM MCF/day.	DETAILS OF WORK Index, show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coments, and all other important proposed work) 94-2302! with 4 holes per foot. No ted 2264-2274! with 4 holes per foot. Perforated 2238-2250! with 4 holes owing 372 MCF/day. Sandfraced through with 17,700 gallons water and 30,000# if with 2,300 gallons water. Breakdown off, treating pressure 1050#, injection off. After treatment flowing 7,460 ive approval in writing by the Geological Survey before operations may be commenced. EER DRILLING CORP.
1 understand the Company BEI Address 40	Perforated 22' gas. Perfora Show of gas. per foot. Fl perforations sand, flushed pressure 2650 rate 35.5 BPM MCF/day.	DETAILS OF WORK Index, show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coments, and all other important proposed work) 94-2302! with 4 holes per foot. No ted 2264-2274! with 4 holes per foot. Perforated 2238-2250! with 4 holes owing 372 MCF/day. Sandfraced through with 17,700 gallons water and 30,000# if with 2,300 gallons water. Breakdown off, treating pressure 1050#, injection off. After treatment flowing 7,460 ive approval in writing by the Geological Survey before operations may be commenced. EER DRILLING CORP.

