

APPROVED

JUN 1956

(SUBMIT IN TRIPLICATE)

Land Office Santa Fe
Lease No. NM 04224
Unit Quitau

W. B. LONG
ACTING DISTRICT ENGINEER

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Subsequent Report of Sand-Oil Treatment	x

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 4th, 1956

Well No. 11 is located 1316 ft. from [N] line and 1289 ft. from [E] line of sec. 3

NE/4 NE/4 Sec. 3
(1/4 Sec. and Sec. No.)

25N
(Twp.)

8W
(Range)

N.M.P.M.
(Meridian)

Ballard
(Field)

San Juan
(County or Subdivision)


New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 7004 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

4-14-56 TD 2766'. Flowing 301 MCF/day. Sand-oil treated from 2715' to 2766' with 17,635 gallons diesel oil and 42,765# sand, flushed with 2,765 gallons diesel oil. Maximum treating pressure 2250#, final pressure 900#, injection rate 30 barrels per minute. After 10 hours flowing 6,000 MCF/day.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company BENSON-MONTIN

Address 405 1/2 West Broadway

Farmington, New Mexico

By [Signature]

Title Field Superintendent

