

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other Instructions on reverse side)Form approved.
Bureau Form No. 42-11424

5. LEASE DESIGNATION AND SERIAL NO.

NM 036254

6. IN INDIAN, ALLOTTEE OR TRUST NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER ☒ WATER INJECTION WELL	7. UNIT AGREEMENT NAME Control Bisti
2. NAME OF OPERATOR: Hixon Development Co.	8. FARM OR LEASE NAME CBU
3. ADDRESS OF OPERATOR: 341 Milam Bldg, SAN ANTONIO, TX 78205	9. WELL NO. W1 5
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1319' PSL & 1315' PWL SEC 10, T25N R12W SAN JUAN Co., N.M. NM PM	10. FIELD AND POOL, OR WILDCAT Bisti Gallup
12. PERMIT NO.	11. SEC., T., R., M., OR BLM, AND SURVEY OR AREA Sec 10, T25N R12W
15. ELEVATIONS (Show whether DT, RT, GR, etc.) 6212 DF	12. COUNTY OR PARISH SAN JUAN
	13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well is no longer Necessary to Unit.
We intend to plug & abandon this well as
Follows:

1. Squeeze Perf 4742 - 4846
2. Spot loss plug inside Csg @ top of P1 Lookout
3. Cut & Pull 4 1/2" Csg.
4. Place Plug 50' inside Stub to 50' Above Stub
5. Place 150' plug over top of P1
6. Set P&A marker w/ 10' surface Plug
7. Clean Loc.

DIST. 3

I hereby certify that the foregoing is true and correct.

SIGNED

TITLE

DATE

(Leave space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUN 4 1974

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.