

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well <input type="checkbox"/> gas well <input checked="" type="checkbox"/> other
2. NAME OF OPERATOR J. Gregory Merrion & Robert L. Bayless
3. ADDRESS OF OPERATOR P.O. Box 507, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 790 FSL & 1830 FWL AT TOP PROD. INTERVAL: same AT TOTAL DEPTH: same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input checked="" type="checkbox"/>
(other)	

5. LEASE NM 16464
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME Crow Mesa
9. WELL NO. 2
10. FIELD OR WILDCAT NAME Ballard Pic. Cliffs
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 34, T25N, R8W
12. COUNTY OR PARISH San Juan
13. STATE N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD) 7237' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

08-23-79 Abandoned wellsite by filling 2-7/8" casing from bottom of Pictured Cliffs @ 2580' to surface with 50 sacks of Class "B" cement w/8% bentonite, then squeezed perfs. Dry hole marker was erected, location was leveled. Will re-seed surface per B.L.M. specifications at appropriate planting time.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Alvin S. L. TITLE Engineer DATE May 1, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

See Instructions on Reverse Side

NMCCG

RECEIVED  
DEC 13 1984  
OIL & GAS DIV.  
DIST. 3

APPROVED  
AS AMENDED

DEC 12 1984

M. MILLENBACH  
AREA MANAGER

RECEIVED  
MAY 2 1980  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N.M.