

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil well ☐ gas well ☒ other ☐2. NAME OF OPERATOR  
Jerome P. McHugh3. ADDRESS OF OPERATOR  
Box 208, Farmington, NM 874014. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
1850' FSL - 1520' FWL  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4-6-80

TD 6000'. Ran IES and CDL and SNP logs by GO Wireline. Ran 149 jts 4-1/2" OD 10.5# K-55 8R csg. TE 6034.52' set @ 6008' RKB. Reciprocated pipe and had good mud returns on 1st stage. Preflushed hole w/10 bbls CW-100. Cemented w/250 sx class "B" w/4% gel w/1/4# cello flake per sx followed by 150 sx class "B" w/1/4# cello flake per sx. Estimated cement top - 4100'. Bumped plug w/1800 psi. Float held OK. Opened Dowell DV @ 3970' w/1600 psi. POB 4:45 a.m. 4-7-80. Total slurry 557 cu ft.

4-7-80

Finished circulating hole. Cemented 2nd stage through DV tool @ 3910' w/5 bbls CW-100 followed by 400 sx 65-35 w/12% gel w/1/4# cello flake per sx. Total slurry 1200 cu ft. Had good mud returns during 2nd stage. Circulated trace of cement. Bumped plug w/2500 psi. Held OK. POB 8:55 a.m. Set slips, cut off pipe. Rig released @ 9:40 a.m. 4-7-80.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED Thomas A. Duga TITLE Agent DATE 4-7-80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

NMOCG