

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR
Jerome P. McHugh

3. ADDRESS OF OPERATOR
Box 208, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 790' FNL - 1850' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) csg ☐

SUBSEQUENT REPORT OF:


☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

APR 21 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-16-80

Laid down drill pipe. Rigged up casing crew. Ran 152 jts 4-1/2" OD 10.5# K-55 8R csg. TE 6135.74' set @ 6130' RKB. Preflushed hole w/10 bbls CW-100. Cemented w/250 sx class "B" w/4% gel w/1/4# cello flake per sx. Total slurry 565 cu ft.

Reciprocated pipe and had good mud returns while cementing. Bumped plug w/1500 psi - held OK. POB 6:30 p.m. Opened DV tool @ 4120' w/1600 psi @ 7:10 p.m. Circulated 3 hrs w/mud pump.

Cemented second stage thru Dowell DV tool @ 4120'. Preflushed hole w/10 bbls CW-100. Cemented w/400 sx 65-35 w/12% gel w/1/4# cello flake per sx. Total slurry 1203 cu ft. Had good mud returns while cementing. Bumped plug w/2500 psi. Set @ _____ Ft.

Subsurface Safety Valve: Manu. and Type _____

Didn't hold. Held on third time. POB 10:45 p.m. Set slips. Released rig @ 12:30 a.m. 4-16-80 Est. cement top 600'

SIGNED Jim L. Jacobs TITLE Agent

DATE 4-17-80

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

ACCEPTED FOR RECORD

JUN 6 1980

FARMINGTON DISTRICT