

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well

2. NAME OF OPERATOR

Southern Union Exploration Company

3. ADDRESS OF OPERATOR

P.O. Box 2179 Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FSL & 660' FEL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Set & cement surface casing ☐

SUBSEQUENT REPORT OF

**RECEIVED**  
MAY 23 1983

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

15. ELEVATIONS (SHOW DF, KDB, AND WD)

291' C.L.

5. LEASE

NM-33027

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

South Bisti

9. WELL NO.

#1

10. FIELD OR WILDCAT NAME

Wildcat Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 3-T25N-R13W N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud 12 1/4" Surface hole 4:30 PM 5/17/83. Drill 12 1/4" hole to 345'. Ran 8 joints 8 5/8" 32#/ft J-55 surface casing @ 337'. Cemented w/235 sks (277 cuft) Class B w/2% CaCl<sub>2</sub> & 1/4#/sk celloflake. Circulate 15 bbl cement to surface. Plug down @ 2:45 AM 5/18/83. Pressure test casing & BOP to 1000 psi & held 30 min. Drilled out cement & drilling 7 7/8" hole.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drlg. Supervisor

DATE 5/19/83

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD

NMOCC

MAY 31 1983

\*See Instructions on Reverse Side

FARMINGTON DISTRICT

BY