UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS	5. LEASE NOO-C-14-20-5197 6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo 7. LINIT AGREEMENT NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.) 1. oil gas well other 2. NAME OF OPERATOR Union Oil Company of California 3. ADDRESS OF OPERATOR P. O. Box 2620 - Casper, WY 82602-2620 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 790' FNL & 1000' FWL (NW NW) AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	Navajo 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME Navajo - D30 9. WELL NO. 9 10. FIELD OR WILDCAT NAME Basin Dakota 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 30, T.25N., R.10W. 12. COUNTY OR PARISH San Juan New Mexico 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6623' GR (Ungraded)
MULTIPLE COMPLETE CHANGE ZONES ABANDON*	rectionally drilled, give subsurface locations and
MIRU Four Corners Drilling Company's rotary hole at 9:15 a.m., 9-7-83. Drilled to 766 POOH. Ran and cemented 18 joints and 1 piece (746 8RD, ST&C, new, seamless casing at 757.99' Maximum PDP 700#. Displaced with 42-1/2 by throughout. Circulated 200 sacks to pit. Released pressure and float held O.K. C.I. 9-7-83. Preceded cement with 200 bbls. of mud flush. W.O.C.	Circulated 1/2 hour and 5.99') of 8-5/8", 24#, J-55, with 500 sacks of cement. Ols. fresh water with returns Bumped plug with 1100 psi. P. & J.C. at 8:40 p.m. on
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED R. G. Ladd, Ir. Superint endent (This space for Federal or State office)	ing date9-8-83
	ACCEPTED FOR RECORD

SEP 14 1983