

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.


SUBMIT IN TRIPLICATE

Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

Name of Operator
Pro NM Energy, Inc.

Address and Telephone No.
460 St. Michael's Dr., #300 Santa Fe, NM

Location of Well (Footage, Sec., T., R., M., or Survey Description)
740' FSL, 1860' FEL
0 Sec. 23, T25N, R11W



5. Lease Designation and Serial No.
NO-G-9909-1357

6. If Indian, Allottee or Tribe Name
Navajo

7. If Unit or CA, Agreement Designation

8. Well Name and No.
Bisti 2

9. API Well No.
30-045-25784

10. Field and Pool, or Exploratory Area
Bisti Lower Gallup

11. County or Parish, State
San Juan

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input checked="" type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other _____
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Pro NM Energy, Inc., as operator of the Bisti 2, plans to plug and abandon the subject well following the procedure shown below with the intention of being able to re-enter the well at a future date.

Set a 20 sack cement plug on top of the cast iron bridge plug at 4921 feet.
~~Set a 20 sack cement plug at 3950 feet.~~
~~Set a 20 sack cement plug at 350 feet.~~
Cut off the casing head below ground level and weld a plate with a monument over the top of the casing.
Clean up and reclaim location and re-seed according to Allottee or BIA specifications.

This work will be performed as soon as concurrence is received from the BIA and a rig becomes available.

14. I hereby certify that the foregoing is true and correct

Signed

Director of Operations
Title _____

Date

9/14/00

(This space for Federal or State office use)

Title

Date

9/19/00

Approved by

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT
FARMINGTON DISTRICT OFFICE
1235 LA PLATA HIGHWAY
FARMINGTON, NEW MEXICO 87401

Attachment to notice of Intention to Abandon:

Re: Permanent Abandonment

Well: 2 Bisti

CONDITIONS OF APPROVAL

1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal and Indian Lease."
2. Mike Flanikan with the Farmington Office is to be notified at least 24 hours before the plugging operations commence (505) 599-8907
3. The following modifications to your plugging program are to be made:
 - a) Spot a cement plug from 4921' - 4746' to cover the Gallup top @ 4796'.
 - b) Spot a cement plug from 2097' - 1997' to cover the Mesaverde top @ 2047'.
 - c) Spot a cement plug from 1382' - 1282' to cover the Pictured Cliffs top @ 1332'.
 - d) Spot a cement plug from 1103' - 1003' to cover the Fruitland top @ 1053'.
 - e) Spot a cement plug from 597' - 262' to cover the Ojo Alamo interval and the surface casing shoe.
 - f) Place the surface plug from 50' to surface.

Office Hours: 7:45 a.m. to 4:30 p.m.