

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
Hixon Development Company
3. ADDRESS OF OPERATOR
P.O. Box 2810, Farmington, NM
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 330' FNL, 2310' FEL 17-25-12
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

(other) Drilling Progress

RECEIVED

MAY 03 1984

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud well at 12:30 am 4/7/84. Drill 12-1/4" hole to 342'. Ran 323' 8-5/8" 24# K-55 8rd surface casing. Install guide shoe and centralizers on tops of 1st and 3rd joints. Casing set at 338'. Cement surface casing using 175 sacks (206.5 cubic feet) Class B with 2% CaCl. Circulated cement to pit. Shut well in. WOC.

RECEIVED

MAY 11 1984

OIL CON. DIV.

Subsurface Safety Valve: Manu. and Type _____

DIST. 3

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Bruce DeWentha

TITLE Petroleum Engineer

DATE 4/18/84

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAY 10 1984

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

BY

SMH

NR000