

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM 68764	
2. NAME OF OPERATOR JEROME P. McHUGH		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo Trust	
3. ADDRESS OF OPERATOR P O Box 809, Farmington, NM 87499		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1750' FNL - 1750' FEL		8. FARM OR LEASE NAME Bettin' on Bisti 30	
14. PERMIT NO.		9. WELL NO. 7	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6445' GL		10. FIELD AND POOL, OR WILDCAT Bisti Lower Gallup	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 30, T25N, R11W, NMPM	
		12. COUNTY OR PARISH San Juan	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) TD, 5 1/2" csg. & cement. ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

See attached for details of TD, 5 1/2" csg. & cement.

18. I hereby certify that the foregoing is true and correct

SIGNED James S. Hazen

TITLE Field Supt.

DATE 12/3/87

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

\*See Instructions on Reverse Side

JEROME P. McHUGH  
P O BOX 809  
FARMINGTON, NEW MEXICO 87499-0809  
505 326-7793

Reached TD of 5200' on 11/30/87.

Ran 14 jts. (564.04') of 5-1/2", 17#, 8 rd, ST&C csg. &  
113 jts. (4639.49') of 5-1/2", 15.5#, 8 rd, ST&C csg.

Set at 5199' KB.

Circulated with rig for 1 hr.

Rigged up Western Co. & cemented as follows:

Pumped 10 bbl. mud flush followed by

350 sx 50/50 poz w/ 2% gel, 6-1/4#/sk gilsonite &  
1/4#/sk celoflake (487 cu.ft.).

Plug down at 9:15 PM 12/1/87.

Opened DV tool at 3148' KB & circulated w/ rig 3 hrs.

Pumped 10 bbl. mud flush followed by

250 sx 65/35 poz w/ 12% gel & 1/4#/sk celoflake and  
100 sx 50/50 poz w/ 2% gel, 6-1/4#/sk gilsonite & 1/4#/sk  
celoflake (794 cu.ft.)

Plug down at 12:50 PM, 12/2/87.

Full returns throughout cement job, w/ show of cement on  
both stages.

Rigged down BOP & set clips.

Rig released at 2:00 AM, 12/2/87.