the following manner:  1) Plug will be set from the pumping 140 sks. (165.2  2) After cement has set up,  3) Cut off wellhead and ins	TitkArea Engineer		u.ft.) by mixing	and :	1994	
the following manner:  1) Plug will be set from the pumping 140 sks. (165.2  2) After cement has set up,  3) Cut off wellhead and ins  14. I hereby certify that the foregoing is true.  Signed	bottom perforations (1205') to the scu.ft.) of Class "B" cement.  tag top and refill if necessary.  tall a regulation dry hole marker.  TitleArea Engineer  use)	surface (109.9 c	u.ft.) by mixing	and .	1994	
the following manner:  1) Plug will be set from the pumping 140 sks. (165.2  2) After cement has set up,  3) Cut off wellhead and ins  14. I hereby certify that the foregoing is true.  Signed	bottom perforations (1205') to the scu.ft.) of Class "B" cement.  tag top and refill if necessary.  tall a regulation dry hole marker.  TitleArea Engineer  use)	surface (109.9 c	u.ft.) by mixing	and .	1994	
the following manner:  1) Plug will be set from the pumping 140 sks. (165.2  2) After cement has set up,  3) Cut off wellhead and ins  14. I hereby certify that the foregoing is true  Signed Heartif Mills  Gregory E. McIntosh	bottom perforations (1205') to the scu.ft.) of Class "B" cement. tag top and refill if necessary. tall a regulation dry hole marker.  and correct  Title Area Engineer	surface (109.9 c	u.ft.) by mixing	and .	1994	
the following manner:  1) Plug will be set from the pumping 140 sks. (165.2  2) After cement has set up,  3) Cut off wellhead and ins	bottom perforations (1205') to the scu.ft.) of Class "B" cement. tag top and refill if necessary. tall a regulation dry hole marker.	surface (109.9 c	u.ft.) by mixing	and .	1994	
the following manner:  1) Plug will be set from the pumping 140 sks. (165.2  2) After cement has set up,  3) Cut off wellhead and ins	bottom perforations (1205') to the scu.ft.) of Class "B" cement. tag top and refill if necessary. tall a regulation dry hole marker.	surface (109.9 c	u.ft.) by mixing	and :		
the following manner: 1) Plug will be set from the pumping 140 sks. (165.2 2) After cement has set up,	bottom perforations (1205') to the scu.ft.) of Class "B" cement. tag top and refill if necessary.	surface (109.9 c	<u> </u>	and ::3		
the following manner: 1) Plug will be set from the pumping 140 sks. (165.2 2) After cement has set up,	bottom perforations (1205') to the scu.ft.) of Class "B" cement. tag top and refill if necessary.		<u> </u>	and ::3		
the following manner: 1) Plug will be set from the pumping 140 sks. (165.2 2) After cement has set up,	bottom perforations (1205') to the scu.ft.) of Class "B" cement. tag top and refill if necessary.		<u> </u>	and ::3		
the following manner: 1) Plug will be set from the pumping 140 sks. (165.2 2) After cement has set up,	bottom perforations (1205') to the scu.ft.) of Class "B" cement. tag top and refill if necessary.		<u> </u>	and ::3		
the following manner: 1) Plug will be set from the pumping 140 sks. (165.2 2) After cement has set up,	bottom perforations (1205') to the scu.ft.) of Class "B" cement. tag top and refill if necessary.		<u> </u>			
the following manner: 1) Plug will be set from the pumping 140 sks. (165.2 2) After cement has set up,	bottom perforations (1205') to the scu.ft.) of Class "B" cement. tag top and refill if necessary.		<u> </u>		en e	
the following manner: 1) Plug will be set from the pumping 140 sks. (165.2 2) After cement has set up,	bottom perforations (1205') to the scu.ft.) of Class "B" cement. tag top and refill if necessary.		<u> </u>			
the following manner: 1) Plug will be set from the pumping 140 sks. (165.2	bottom perforations (1205') to the scu.ft.) of Class "B" cement.		<u> </u>			
the following manner:  1) Plug will be set from the	bottom perforations (1205') to the		<u> </u>			
the following manner:			<u> </u>			
the following manner:			<u> </u>			
Giant Exploration & Produ	ction Company plans to plug and ab	andon the abov	e referenced w	ell in		
un ectionally utilieu, give subsurface local	ions and incasured and true vertical deptils t	or all markers allu	somes per miem to			
3. Describe Proposed or Completed Operationals dispersionals design as the complete of the com	tions (Clearly state all pertinent dates, includitions and measured and true vertical depths f	ing estimated date	of starting any prop	oosed work. If	well is	
		Complet	ion or Recompletic	on Report and	Log form.)	
Final Abandonment Notice	Other		te: Report results of multiple completion on Well			
Subsequent Report	Altering Casing		onversion to Injecti	on		
X Notice of Intent Subsequent Report	Casing Repair	=	ater Shut – Off	<del>-</del> 5		
	Recompletion Plugging Back		ew Construction on-Routine Fracti	ıring		
[V] Nation of Leaves	X Abandonment		nange of Plans			
TYPE OF SUBMISSION		FACTION	anna ac mi-			
			e, KEFUKI,		ZV DVI	
	OX(s) TO INDICATE NATURI	F OF NOTICE			TR DAT	
790' FNL, 790' FEL, Sec. 20, T25N, R11W			San Juan, New Mexico			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			11. County or Parish, State			
P.O. Box 2810, Farmington, New Mexico 87499 (505)326-3325			Basin Fruitland Coal			
2. Name of Operator Giant Exploration & Production Company 3. Address and Telephone No.			30-045-27915  10. Field and Pool, or Exploratory Area			
						2. Name of Operator
1. Type of Well Oil Well X Gas Well Other			Carson Unit 20 Well #341			
SUBMIT IN TRIPLIC	AIE	-	8. Well Name and No.			
Use "APPLICATION FOR PERM	IIT * for such proposals		_	_		
Do not use this form for proposals to d	rill or to deepen or reentry to a different rese	ervoir, 7.	Navajo Allottee 7. If Unit or CA. Agreement Designation			
SUNDRY NOTICES AN	D REPORTS ON WELLS					
BUREAU OF LAND MANAGEMENT			6. If Indian, Allottee or Tribe Name			
DEPARTMENT OF THE INTERIOR			14-20-603-1440			
	UNITED STATES			and Serial No	).	
DEPARTMENT OF	ATES		Expires: March 31	<del>- / -</del>		
DEPARTMENT OF	ATES			Budget Bureau No. 1004-0135		
DEPARTMENT OF	ATES		_	o. 1004–0135 <sub>/</sub>		

fictious or fraudulent statements or representations as to any maner within its jurisdiction

\*See Instruction on Reverse Side

APPROVED

NOV 2 স ভিচৰ