Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

Completion or Recompletion Report and Log form.)

5. Lease Designation and Serial No.

6. If Indian, Allottee or Tribe Name

NM 0468000	6
------------	---

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals

Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Oil Well X Gas 8. Weli Name and No. 2. Name of Operator Buena Suerte 4L Com #1 Giant Exploration & Production Company 9. API Well No. 3. Address and Telephone No. 30-045-28077 PO Box 2810, Farmington, N.M. (505) 326-3325 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Basin Fruitland Coal 11. County or Parish, State 1625' FSL, 1085' FWL, Sec. 4, T25N, R11W

			Jan Juan, New Mexico
12.	CHECK APPROPRIATE BOX	s) TO INDICATE NATURE OF NOTICE, RE	PORT, OR OTHER DATA
	TYPE OF SUBMISSION	TYPE OF ACT	ION
	Notice of Intent	Abandonment	Change of Plans
	X .	Recompletion	New Construction
	Subsequent Report NOV	Digging Back	Non-Routine Fracturing
		Casing Repair	☐ Water Shut-Off
	Final Abandonment Notce)	Altering Casing	Conversion to Injection
		Alox Drilling Progre	SS Dispose Water
	015	, 🗳	(Note: Report results of multiple completion on Well

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled out from under casing with 6-1/4" bit September 20, 1990. Drilled to TD of 1437'. Ran 35 jts. (1454.48') of 4-1/2", 9.5#, J-55, 8rd, ST&C casing. BakerLoked cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. Ran centralizers on tops of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1436', PBD at 1400.2'. Cemented casing as follows: Mixed and pumped 75 sks. (154 cu. ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane flakes. Tailed in with 85 sks. (100 cu. ft.) of Class "B" cement containing 2% CaCl2 and 1/4#/sk. cellophane flakes. Cement circulated to surface. Pressure tested casing to 3500 psi for 15 minutes. Test ok. Ran Gas Spectral/Gamma Ray log with Collar Locator. Log tops as follows: Fruitland - 1207', Fruitland Basal Coal - 1306', Pictured Cliffs - 1333'. Waiting on completion operations.

4. I hereby certify that the foregoing is true and correct

Signed Older Date OCT 2 4 1990

(This space for Federal or State SMCFLSET a most

ACCEPTED FOR RECOF

Approved by _____ Title _____ Date _____ Conditions of approval, if any:

FARMINGTON RESOURCE AREA

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.