

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Giant Exploration & Production Company

3. Address and Telephone No.

P.O. Box 2810, Farmington, New Mexico 87499 (505) 326-3325

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

790' FNL, 790' FEL, Sec. 24, T25N, R13W

5. Lease Designation and Serial No.

NM 58138

6. If Indian, Allottee or Tribe Name

N.M.

7. If Unit or CA, Agreement Designation

8. Well Name and No.

West Bisti Coal 24 #1

9. API Well No.

30-045-28515

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Drilling Progress

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled out from under casing with 6-1/4" bit March 5, 1991. Drilled to TD of 1450'. Ran Compensated Density-Neutron logs with gamma ray. Log tops as follows: Fruitland - 1093', Basal Fruitland Coal - 1272', Pictured Cliffs - 1330'. Ran 37 jts. (1445.48') of 4-1/2", 11.6#, K-55, 8rd, LT&C casing. BakerLok cement nosed guide shoe on bottom and float collar on top of 1st jt. Ran centralizers on tops of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1442', PBD at 1398.53'. Cemented casing as follows: Mixed and pumped 80 sks. (164 cu. ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane flakes. Tailed in with 80 sks. (94 cu. ft.) of Class "B" cement containing 2% CaCl₂ and 1/4#/sk. cellophane flakes. Cement circulated to surface. Pressure tested casing to 3500 psi for 15 minutes. Test ok. Waiting on completion operations.

ACCEPTED FOR RECORD

APR 12 1991

FARMINGTON RESOURCE AREA

14. I hereby certify that the foregoing is true and correct

Signed Aldrich L. Kuchera Title President

(This space for Federal or State office use)

BY [Signature] Date MAR 18 1991

Approved by _____ Title _____ Date _____
Conditions of approval, if any: _____