

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

NM 61273

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

WestBisti Coal 23 #1

9. API Well No.

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan, N.M.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Giant Exploration & Production

3. Address and Telephone No.

P.O. Box 2810, Farmington, NM (505)326-3325

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2510' FNL, 1850' FEL

SEC. 23, T25N, R13W, NMPM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Drilling Progress

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled out from under casing with 6 1/4" bit September 9, 1992. Ran compensated density-neutron logs with caliper and gamma ray. Log tops as follows: Fruitland 1031', Basal Fruitland Coal- 1196', Pictured Cliffs- 1263'. Ran 32 jts(1370.89') of 4 1/2", 9.5#, J-55, 8RD, ST&C casing. Bakerloked cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. Ran centralizers on top 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1366.49', PBD at 1330.49'. Cemented casing as follows: mixed and pumped 80 sks (164.8 cu ft) Class "B" cement containing 2% thriftment and 1/4 #/sk cellophane flakes. Tailed in with 75sks (88.5 cu ft) Class "B" cement contains 2% CaCl₂ and 1/4 #/sk cellophane flakes. Cement circulated to surface. Pressure tested casing to 3500 psi for 15 minutes. Test okay. Waiting on completion operations.

14. I hereby certify that the foregoing is true and correct

Signed Jeffrey R. Vaughan
(This space for Federal or State office use)

Title Engineering Manager

Approved by _____
Conditions of approval, if any:

Title _____

Date SEP 18 1992

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMCCO