

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other	5. Lease Designation and Serial No. NM - 25450
2. Name of Operator Giant Exploration & Production Company	6. If Indian, Allottee or Tribe Name
3. Address and Telephone No. P.O. Box 2810, Farmington, N.M. 87499 (505) 326-3325	7. If Unit or CA, Agreement Designation
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 2510' FSL, 790' FWL, Sec. 23, T25N, R12W	8. Well Name and No. Bisti Coal 23 No.2
	9. API Well No.
	10. Field and Pool, or Exploratory Area Basin Fruitland Coal
	11. County or Parish, State San Juan, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Drilling Progress

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled out from under casing with 6-1/4" bit on November 6, 1992. Ran Compensated Density-Neutron logs with caliper and gamma ray. Log tops as follows: Fruitland - 948', Basal Fruitland - 1120', and Pictured Cliffs - 1169'. Ran 30 jts. (1242.94') 4-1/2", 9.5#, J-55, 8rd, ST&C casing. Bakerloked cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. Ran centralizers on top of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1237.94', PBD at 1212.24'. Mixed and pumped 70 sks. (144.2 cu ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk cellophane flakes. Tailed in with 70 sks. (82.6 cu ft.) Class "B" cement containing 2% CaCl₂ and 1/4#/sk cellophane flakes. Circulated cement to surface. Pressure tested casing to 3500 psi for 15 minutes. Waiting on completion.

14. I hereby certify that the foregoing is true and correct

Signed Jeffrey R. Vaughan Title Engineering Manager

Date NOV 16 1992

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

FARMINGTON RESOURCE AREA

BY

Smm