PORM APPROVED UNITED STATES Form 3160-5 dget Bureau No. 1004-0135 5 BLM (June 1990) DEPARTMENT OF THE INTERIOR Expires: March 31, 1993 1 File **BUREAU OF LAND MANAGEMENT** 5. Lease Designation and Sorial No. NM-76866 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well ☐ Well X Well 8. Well Name and No. Other Alamo Com #90 2. Name of Operator 9. API Well No. Dugan Production Corp. 30 045 28806 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area P.O. Box 420, Farmington, NM 87499 (505) 325-1821 Basin Fruitland Coal 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State 2510' FSL & 1850' FWL (Unit K) 4-25N-13" San Juan, New Mexico CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION Notice of Intent Abandonment Change of Plans Recompletion New Construction X Subsequent Report Non-Routine Fracturing Plugging Back Water Shut-Off Casing Repair Final Abandonment Notice Altering Casing Conversion to Injection Other Spud & surface casing Dispose Water (Note, Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Move in and rig up Wayne Smith Drilling Company. Spudded 9-1/8" hole at 12:00 Noon 11-23-92. Drilled to 130'. Ran 3 jts. 7" OD, 23#, K-55, 8 Rd, ST&C casing (T.E. 126') landed at 128' GL. Cemented with 50 sx class "B" with 2% CaCl, (total cement slurry = 59 cu.ft.). P.O.B. at 4:30 P.M. 11-23-92. Circulated 2 bbls cement to surface. W.O.C. 6 hrs. Nippled up BOP and pressure tested surface casing and BOP 600 psi 30 minutes - held OK. 14. I hereby cequify that the foregoing is true and correct Vice-President This i Federal or State/office use) Approved by Conditions of approval, if any: ACCEPTED FOR AFLICE Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. *See Instruction on Reverse Side

> -ahmingfon hebousch ahre iv Sm