

			X

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office New Mexico
Lease No. 0111-A
Unit E/2

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 27, 1962, 19

J. Glenn Turner - Quantius

Well No. 1-26 is located 790 ft. from [N] line and 790 ft. from [E] line of sec. 26

NE/4 Section 26
(¼ Sec. and Sec. No.)

T 26-N R 7-W
(Twp.) (Range)

N.M.F.M.
(Meridian)

Basin Dakota
(Field)

Rio Arriba County
(County or Subdivision)

New Mexico
(State or Territory)

(So. Blanco Ext. P. C.)

The elevation of the derrick floor above sea level is 6,560 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

November 18, 1961 - Well spudded at 2:00 p.m. Set 9 joints 8-5/8" 24# J-55 casing at 292'. Cemented with 200 sacks CACL₂ cement. Circulated 10 sacks. WOC. Tested casing with 800 psi. Found OK, and continued drilling with rotary rig.

December 10, 1961 - after drilling to 7420' - concluded this well would not produce from formations below Pictured Cliffs. On 12/13/61 spotted cement plug in interval 7420'-6990' with 70 sacks 50-50 pozmix with 4% gel. Spotted plug in interval 2760 - 2860. Used 50 sack cement with 2% CACL₂. Completed at 9:50 a.m.

December 14, 1961 - Found top of cement plug at 2695'. Drilled to a Plugged Back Total Depth of 2760'. On 12/15/61 ran 87 joints 4-1/2" 9.5# J-55 STC Casing, guide shoe and float shoe. Landed casing at 2760'. Cemented with 100 sacks neat cement. Displaced cement with 43 barrels water. Bumped plug with 2000 psi. Float held. See Page 2 for completion information.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company E. Glenn Turner
Address P. O. Box 728
Farmington, New Mexico

By [Signature]
C. Beeson Neal, Agent in
Title Farmington