

(SUBMIT IN TRIPLICATE)

Indian Agency Jicarilla

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee _____

Lease No. Cont. 237

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	<input type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	<input type="checkbox"/>	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	<input type="checkbox"/>	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	<input type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	<input type="checkbox"/>	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<input type="checkbox"/>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 7, 19 62

Well No. Betsy 4 is located 330 ft. from SW line and 1980 ft. from W line of sec. 29


SW 29 (1/4 Sec. and 1/4 Sec. No.) 27N (Twp.) 1E (Range) NMPM (Meridian)
Puerto Chiquito (Field) Rio Arriba (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 7098 ft. g1

DETAILS OF WORK

(State names of anticipated depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drill 11" hole and set 40' of 7-5/8" csng w/ 25 sax cement
Drill 6-3/4" hole and set 800' of 5-1/2" csng w/ 50 sax
Drill 4-3/4" hole to approx 1800' to test Gallup. If productive will set 3-1/2" csng on packer shoe w/ 30 sax.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company R. L. Bayless

Box 1541

Address Farmington, N M

By R L Bayless

Title _____