

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Indian Agency \_\_\_\_\_

Jicarilla Tribal

Allottee \_\_\_\_\_

Lease No. Jicarilla Contract 237


SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL _____	SUBSEQUENT REPORT OF WATER SHUT-OFF _____
NOTICE OF INTENTION TO CHANGE PLANS _____	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____	SUBSEQUENT REPORT OF ALTERING CASING _____
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL _____	SUBSEQUENT REPORT OF REDRILLING OR REPAIR _____
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____	SUBSEQUENT REPORT OF ABANDONMENT _____
NOTICE OF INTENTION TO PULL OR ALTER CASING _____	SUPPLEMENTARY WELL HISTORY _____
NOTICE OF INTENTION TO ABANDON WELL _____	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

U. S. GEOLOGICAL SURVEY  
FARMINGTON, NEW MEXICO

Jicarilla Tribal 237

Farmington, New Mexico-December 13, 1960

Well No. 1 is located 472.9 ft. from S line and 1295 ft. from W line of sec. 20

Lot 4 Section 20  
(4 Sec. and Sec. No.)

T-27-N  
(Twp.)

R-1-E  
(Range)

N.M.P.M.  
(Meridian)

Puerto Chiquito Gallup  
(Field)

Bio Arriba  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 7050 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

As a result of not obtaining oil or gas in commercial quantities, we propose to plug and abandon Jicarilla Tribal 237 No. 1 as follows:

1. Move in pulling unit.
2. Squase open hole section with 100 sacks of cement below cement retainer set in 5-1/2" casing above previous squase perforations.
3. Run free point to determine if pipe can be cut-off and pulled from below water sand.
4. Spot 10 sacks calcium chloride cement plug across casing stub.
5. Mix mud and fill hole.
6. Either set Baker Model X GI wireline bridge plug in a hard interval below water sand and run with dump bailer and one sack of calcium chloride cement on top or run umbrella bridge above casing stub depending on conditions encountered.

(OVER)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Box 480

Farmington, New Mexico

ORIGINAL SIGNED BY  
R. M. Bauer, Jr.

By \_\_\_\_\_

Title Area Engineer