

(November 1983)
(Formerly 9-331)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

BU. 1004-1. TRIPPLICATE
(Other instructions on reverse side)

Expires August 31, 1985
1004-0135

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER		7. UNIT AGREEMENT NAME Rincon Unit
2. NAME OF OPERATOR Unocal		8. FARM OR LEASE NAME Rincon Unit
3. ADDRESS OF OPERATOR 3300 North Butler Ave. Suite 200		9. WELL NO. 73
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1800' FNL & 900' FEL		10. FIELD AND POOL, OR WILDCAT Blanco Pictured Cliffs South Basin Fruitland Coal
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 33, T27N & R7W
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6866 GL		12. COUNTY OR PARISH Rio Arriba
		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

(Other) Recomplete uphole Fruitland Coal ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

It is proposed to set a bridge plug above the Pictured Cliffs formation and recomplete to the Basin Fruitland Coal formation.

1. MIRUSU
2. Sit BP at 3145'.
3. Run CBL across Fruitland Coal and squeeze as necessary.
4. Perforate 2998' - 3002', 3016' - 22', 3078' - 84', 3122' - 36' w/0.5" holes. Total 120.
5. Frac with 180,000# 20-40 sand in N₂ foam.
6. Flow back and cleanup.
7. TIH with 2 3/8", 4.7#, 8rd, EUE tubing and land at 3100'.
8. Release rig.

RECEIVED
SEP 20 1990
OIL CON. DIV.
DIST. 3

RECEIVED
SEP 23 1990
OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED S. G. Katirgis

TITLE Petroleum Engineer

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE
NMCOO

APPROVED
AS AMENDED
DATE
SEP 17 1990
Ken Townsend
AREA MANAGER

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.