
Form 9-331a (Feb. 1951)



## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Offic	. Santa Fe	
Lease No.	079394	
Unit	San Aven 27-5	Unit
No	14-00,001	01

## SUNDRY NOTICES AND REPORTS ON WELLS

OTICE OF INT	ENTION TO DRILL	X	SUBSEQUENT REPORT OF WATER SHUT-OFF
			1
OTICE OF INT	ENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
	ENTION TO TEST WATER SHUT-O		SUBSEQUENT REPORT OF ALTERING CASING
	ENTION TO RE-DRILL OR REPAIR		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
_	ENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT.
	ENTION TO PULL OR ALTER CASI		SUPPLEMENTARY WELL HISTORY
OTICE OF IN	ENTION TO ABANDON WELL		
	(INDICATE ABOVE I	BY CHECK MARK NAT	URE OF REPORT, NOTICE, OR OTHER DATA)
ell No	5 is located 16	50 ft. from.	N line and 1650 ft. from E line of sec. 34
Clá Sec.	Section 3 Z	(Ran	ge) (Meridian)
<b>Hildcet</b>		Rio Arriba	Hew Magico
(1	field)	(County or Sub	bdivision) (State or Territory)
It	is intended to dri	ll a well t	OF WORK eights, and lengths of proposed casings; indicate mudding jobs, ceme important proposed work)  hrough the Houseverde using rotary tool.
It end dril with 2 q	is intended to dri	ill a well to with gas c	eights, and lengths of proposed casings; indicate mudding jobs, cemeimportant proposed work)  hrough the Macaverde using rotary tools inculation. The Masaverde vill be shot
It end dril with 2 q	is intended to dri ling the Heanverde warts of S.N.G. po	ill a wall to with gos correct. To	eights, and lengths of proposed casings; indicate mudding jobs, cemeimportant proposed work)  hrough the Macaverde using rotary tools inculation. The Masaverde vill be shot
It end dril with 2 q	is intended to dri ling the Hesaverde punts of S.H.G. pu maing Program: 9-5/8" at 172' u 7 at 4870' u	ill a wall to vith gas cor foot. To	eights, and lengths of proposed casings; indicate mudding jobs, ceme important proposed work)  hrough the Hecaverde using rotary tool; irculation. The Hesaverde will be shot tal depth 5535°.
It end dril with 2 q	is intended to drilling the Hesswerds parts of S.H.G. parts of S.H.G. parts of S.H.G. parts of Section 172' to	ill a wall to with gos come foot. To	hrough the Hoseverde using rotary tool directation. The Hoseverde vill be shot tal depth 5535'.
It end dril with 2 q	is intended to drilling the Hesswerds parts of S.H.G. parts of S.H.G. parts of S.H.G. parts of Section 172' to	ill a wall to with gas come foot. To	hrough the Meawerde using rotary tools inculation. The Meawerde vill be shot tal depth 5535'.  Les of regular cement circulated to sure its of regular cement.
It end dril with 2 q	is intended to drilling the Heaverds parts of S.M.G. per taking Program:  9-5/8" at 172' v 7 at 4870' v The Eg of Sect	ill a wall to with gas come foot. To	reights, and lengths of proposed casings; indicate mudding jobs, cemeimportant proposed work)  hrough the Hoseverde using rotary tools inculation. The Heseverde vill be shot tal depth 5535'.  has of regular coment circulated to sure the of regular coment.  Indicated to this well.
It end dril with 2 q	is intended to drilling the Hesaverde purits of S.H.G. per casing Program:  9-5/8" at 172' wat 4870' wat 4	ill a wall to with gas come foot. To	reights, and lengths of proposed casings; indicate mudding jobs, cemeimportant proposed work)  hrough the Hoseverde using rotary tools inculation. The Heseverde vill be shot tal depth 5535'.  has of regular coment circulated to sure the of regular coment.  Indicated to this well.
It end dril with 2 q	is intended to dri ling the Hesaverde puncts of S.H.G. pu  casing Program:  9-5/8" at 172' v  7 at 4870' v  The Ed of Sect  that this plan of work must rece EL PASC MATURAL C  BOX 997	ill a wall to with gas come foot. To	brough the Hoseverde using rotary tools important proposed work)  brough the Hoseverde using rotary tools irculation. The Hoseverde vill be shot tal depth 5535'.  bis of regular coment circulated to sure the of regular coment.  Indicated to this well.  By Mills Market Market and State of St
It end dril with 2 q	is intended to dri ling the Hesaverde puncts of S.H.G. pu  casing Program:  9-5/8" at 172' v  7 at 4870' v  The Ed of Sect  that this plan of work must rece EL PASC MATURAL C  BOX 997	ill a wall to with gas come foot. To	brough the Hoosverde using rotary tool directation. The Hoosverde using rotary tool directation. The Hoosverde vill be shot tal depth 5535'.  Les of regular coment circulated to sure the second to this well.  By Allow Regimeer.  Title Petroleum Engineer.