

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____
Lease No. _____
Unit 18/4 Sec. 25
Lincoln Co. N.M.
1 Sec. 210

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 7, 1952

Well No. 12 is located 1650 ft. from N line and 1550 ft. from W line of sec. 25

18/4 Sec. and Sec. No. 25 27 N (Twp.) 7 E (Range) 105 W (Meridian)
Lincoln (Field) Lincoln (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 6027 ft. 00

DETAILS OF WORK


(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drill to 3/4 inch tubing hole to 110 feet. Set 100 feet of 1 1/4 inch sand case casing. Circulate out with 100 sacks.

Drill to 3/4 inch hole to 3100' or top of Pictured Cliff - set 200, 7 inch casing with 100 sacks regular cement.

Drill 6 inch hole with Cable tools from 3100 to 3200 feet.

Shoot open hole, tamped, with 300 quarts Nitro Gel.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Ralph A. Johnston

Address P.O. Box 513

Lincoln Co., New Mexico

By James W. Copeland
James W. Copeland
Title Supt.