


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. SF 079527-A

Unit _____



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

RECEIVED
MAR 13 1963
U.S. GEOLOGICAL SURVEY
NEW MEXICO

March 7, 1963

Champlin
Well No. 3-35 is located 1060 ft. from [N] line and 1850 ft. from [E] line of sec. 35

Ne/4 Sec. 35 27 N 4 W NMPM
($\frac{1}{4}$ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco Mesaverde Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

Tapicito Pictured Cliffs
The elevation of the derrick floor above sea level is 7092 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled out below 7-5/8" intermediate with gas, drilled to 6230'. Ran 69 joints (223') 4-1/2", 10.5 lb. casing as liner, set liner from 4003.3' to 6226.7' KB., cemented with 340 sacks 50/50 Diamix "A", plug down at 8:50 P.M., 1/29/63.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations are commenced.

Company Consolidated Oil & Gas, Inc.

Address Writer Building

4150 E. Mexico Avenue

Denver 22, Colorado

By William
Title Chief Engineer