	<b>n 9-</b> 8 pril 19	<b>Sec</b>	tion	27
O				

## (SUBMIT IN TRIPLICATE)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Ag		Jica	بلللع	Tri	bal
Conti					
Allottes .					
	Jie	w111			

DOMPKI NO	IICEO A	IND INDIA	ORTS ON WELLS
TICE OF INTENTION TO DRILL		SUBSEQUENT	REPORT OF WATER SHUT-OFF
TICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT	REPORT OF SHOOTING OR ACIDIZING
TICE OF INTENTION TO TEST WATER SHUT	r-off	SUBSEQUENT	REPORT OF ALTERING CASING.
ICE OF INTENTION TO REDRILL OR REPA	UR WELL	SUBSEQUENT	REPORT OF REDRILLING OR REPAIR
fice of intention to shoot or acidiz	<b>E</b>	SUBSEQUENT	REPORT OF ABANDONMENT
TICE OF INTENTION TO PULL OR ALTER O	ASING	SUPPLEMENTA	RY WELL HISTORY
ICE OF INTENTION TO ABANDON WELL	<del>  </del>		0012
(INDICATE ARCV)	FRY CHECK MARK	NATURE OF REPORT	NOTICE, OR OTHER DATA)
UNDICKTE ABOVE	E E CILOR MAINT		
	:		October 23 19.56
Manual 1 n W 1988	:		,
No is located	990ft. fro	$\mathbf{m} \left\{ \begin{array}{c} \mathbf{x} \\ \mathbf{S} \end{array} \right\}$ line and	dft. from \biggreen \biggreen \limits \line of sec
Set Sections 27	27 N	3 W	N.M. P.M.
()4 Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)
engion of Blanco	Ric	Arriba	New Mexico
(Field)	(County	or Subdivision)	(State or Territory)
levation of the derrick floor	i .	(Mac)	
	_		
	DETAI	LS OF WOR	K
	ilve sands; show size	es, weights, and ler ther important pro	gths of proposed casings; indicate mudding jobs, cemen sposed work)
ter setting 5-1/2" casi rvey Top of Cement 0 61 6230'. Set retainer at in Temperature Survey to 1/2" casing with 50 sx stainer at 6085' and rec ment at 5420'. Drilled ested with 1000#. Teste	ive sands; show size of points, and all of the points, and 61.85', no dement. To emented 5-1 out cement of OK, no by	m at 6365'n Temperature cement. Superature 1/2" casing t & plugs i reak.	with 100 sx cement, Temperature Survey and found top of cement 5-1/2" casing with 50 sx cement et retainer at 6161' and recement survey top of cement at 6130'.  with 100 sx cement. Survey to 6330' PBTD.  OCT 26 1956 OIL CON. COM.
er setting 5-1/2" casivey Top of Cement 0 61 230'. Set retainer at Temperature Survey to /2" casing with 50 sx ainer at 6085' and rec sent at 5420'. Drilled ted with 1000%. Teste	ive sands; show size of points, and all of the points, and all of the points of the po	m at 6365;  Temperature coment. Superature 1/2" casing t & plugs i reak.	with 100 sx cement, Temperature Survey and found top of cement 5-1/2" casing with 50 sx cement et retainer at 6161' and recement at 6130'.  with 100 sx cement at 6130'.  with 100 sx cement. Survey to 6330' PBTD.  OCT 26 1956  OIL CON. COM.
vey Top of Cement 0 61 230'. Set retainer at a Temperature Survey to /2" casing with 50 sx cainer at 6085' and recent at 5420'. Drilled sted with 1000\$. Tested with 1000\$. Tested with 1000\$. Tested with 1000\$.	ive sands; show size of points, and all of the points, and all of the points of the po	m at 6365;  Temperature coment. Superature 1/2" casing t & plugs i reak.	with 100 sx cement, Temperature Survey and found top of cement 5-1/2" casing with 50 sx cement et retainer at 6161' and recement at 6130'.  with 100 sx cement at 6130'.  with 100 sx cement. Survey to 6330' PBTD.  OCT 26 1956  OIL CON. COM.
er setting 5-1/2" casivey Top of Cement 0 61230'. Set retainer at Temperature Survey to /2" casing with 50 sx ainer at 6085' and recent at 5420'. Drilled ted with 1000%. Teste marked with 1000%. Teste pany	ive sands; show size of points, and all of the points, and all of the points of the po	m at 6365;  Temperature coment. Superature 1/2" casing t & plugs i reak.	with 100 sx cement, Temperature Survey and found top of cement 5-1/2" casing with 50 sx cement et retainer at 6161' and recement at 6130'.  with 100 sx cement at 6130'.  with 100 sx cement. Survey to 6330' PBTD.  OCT 26 1956  OIL CON. COM.
er setting 5-1/2" casivey Top of Cement 0 61 230'. Set retainer at Temperature Survey to /2" casing with 50 sx ainer at 6085' and recent at 5420'. Drilled ted with 1000%. Teste	ive sands; show size of points, and all of the points, and all of the points of the po	m at 6365 nation of the important prometal process of the comment	gths of proposed casings; indicate mudding jobs, comen proceed work)  with 100 sx cement, Temperature re Survey and found top of cement 5-1/2" casing with 50 sx cement et retainer at 6161' and recement Survey top of cement at 6130'.  with 100 sx cement. Survey to 6330' PBTD.  OCT 26 1956  OIL CON. COM.  cologica Surve DISTOR attorn to be commenced.
rey Top of Cement e 61230'. Set retainer at Temperature Survey to /2" casing with 50 sx ainer at 6085' and recent at 5420'. Drilled ted with 1000#. Teste Magnolia Petrol Pany Regnolia Petrol P. O. Box 633	ive sands; show size of points, and all of the points, and all of the points of the po	m at 6365 nation of the important prometal process of the comment	gths of proposed casings; indicate mudding jobs, comen proceed work)  with 100 sx cement, Temperature Present and Found top of cement 5-1/2" casing with 50 sx cement et retainer at 6161' and recement at 6130'.  with 100 sx cement at 6130'.  with 100 sx cement. Survey to 6330' PBTD.  OCT 26 1956  OIL CON. COM.  cological Surve DIST of Salions has be commenced.

MO. 2003 110

er 1,100 :

•