Form 9-381 a (Feb. 1961)

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Budget Bureau No. 42-R358.4. Form Approved.

Land Office Santa Fe

Lease No. SF 079527

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.		SUBSEC	QUENT REPORT OF WATER SHU	IT-OFF	<u>X X  </u>
NOTICE OF INTENTION TO CHANGE	PLANS	SUBSEC	QUENT REPORT OF SHOOTING	OR ACIDIZING	
NOTICE OF INTENTION TO TEST W	TER SHUT-OFF	SUBSEC	UENT REPORT OF ALTERING (	CASING	
NOTICE OF INTENTION TO RE-DRIL	L OR REPAIR WELL	SUBSEC	UENT REPORT OF RE-DRILLIN	G OR REPAIR	
NOTICE OF INTENTION TO SHOOT	OR ACIDIZE	SUBSEC	UENT REPORT OF ABANDONMI	ENE POEI	WEIII
NOTICE OF INTENTION TO PULL OF	ALTER CASING	SUPPLE	QUENT REPORT OF ABANDONMI		
NOTICE OF INTENTION TO ABANDO	N WELL	i		ID)	
				<u> </u>	1963
•			August 26	u. s. ceclogica falmineton. N	L SURVEY
Champli <b>n</b>		(3.1)			
Well No. 6-25 is loc	ated 1, <b>6</b> 50 ft. fro	m. SX line	and 1, 850 ft. from	w line of sec.	25
NW 25 (34 Sec. and Sec. No.)	27N	.4W	NMPM		
(1/2 Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)		
Basin Dakota Rio Arriba		a	New Mexico		
(Field) (County or Subd		y or Bubdivision)	livision) (State or Territory)		

The elevation of the derrick floor above sea level is 7. 317 ft. 7, 329 DETAILS OF WORK KB

Tapicito Pictured Cliffs

ected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and all other important proposed work)

Spudded 7/29/63. Drilled 17" surface hole to 300, ran 12-3/4" 50% lb. casing to 300', cemented with 274 sx. of regular with 2% CaCl, circulated cement to surface. Drilled Il" hole to 4408'. Ran 8-5/8", 32 lb. casing, set at 4376' KB. Cemented 225 sx reg & 100 sx reg 2% CaC 2 Plug down @ 4 AM - 8/9/63.

