Budget Bureau No. 42-R358.1. Approval expires 11-30-49.

#### Santa Fe

Land Office

### Federal #1 Unit \_\_\_\_\_

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

(SUBMIT IN TRIPLICATE)

# SUNDRY NOTICES AND REPORTS ON WELLS

		SUBSEQUENT RE	PORT OF WATER S	1101-011		
OTICE OF INTENTION TO DRILL		SUBSEQUENT RE	PORT OF SHOOTING	G OR ACIDIZING		
OTICE OF INTENTION TO CHANGE PLANS	T-0FF	SUBSEQUENT RE	PORT OF ALTERING	G CASING		
OTICE OF INTENTION TO RE-DRILL OR REP	AIR WELL	SUBSEQUENT RE	PORT OF REDRILL	ING OR REPAIR		
OTICE OF INTENTION TO RE-DRILL OR REPORTED OR ACIDIZATION TO SHOOT OR ACIDIZAT	Æ	SUBSEQUENT RE	PORT OF ABANDO	NMENT		
OTICE OF INTENTION TO SHOOT OR ACTOR OTICE OF INTENTION TO PULL OR ALTER	CASING	SUPPLEMENTAR	Y WELL HISTORY		X-	
OTICE OF INTENTION TO ABANDON WELL						
						7
(INDICATE ABO)	E BY CHECK MARK	NATURE OF REPORT,	NOTICE, OR OTHER !	DATA)		
•		***************************************	August		, 19	) 
ell No <b>1</b> is located	1 <b>72</b> 0 tr tr.	m Neline and	1000 ft. fro	om (E) line	24 of sec	
ell Nois located	it. iro	mi mile and		( <del>/////</del> //		
	27N	7**	NMPM	/A	Fran	
NE/4 Sec. 24 (½ Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)	Na Mari	665/!/X	Š.
Wildcat	Rio	Arriba		7	SIFFA	1
(Field)		or Subdivision)		(State or Territo	*/ <b>40</b>	
<b>4-</b>		, 6603,	<b>.</b> .	1 % 0	1960	3
ne elevation of the derrick floo	r above sea le	vei is	L.	1 0/2	M. 200	1
<del></del> -				1 -193	in Co. A	Ī
				\ -,	. Sugar	
	DETEK!	TIC OF WORL	7		edding jobs forms	nt⇒
	DETEK!	TIC OF WORL	7	ings; indicate mu	dding jobs come	nt→
tate names of and expected depths to obje	DETA	ILS OF WORI	ths of proposed cas posed work)	sings; indicate on	dding jobs come	nt⊲
tate names of and expected depths to obje	DETA	ILS OF WORI	ths of proposed cas posed work)	sings; indicate on	dding jobs come	<sub>nt-</sub>
tate names of and expected depths to obje	DETA ctive sands; show si- ing points, and all 60° T.D.	ILS OF WORI zes, weights, and leng other important pro 12:15 a.m.	ths of proposed cases of the control	cement a	ad D.V. 8	<sub>nt-</sub>
tate names of and expected depths to obje	DETA	ILS OF WORI zes, weights, and leng other important pro 12:15 a. m. 66' w/150 st	ths of proposed cases work) 6-21-60. LE Posmix	-	4-7%-hil-	
tate names of and expected depths to obje	DETA	ILS OF WORI zes, weights, and leng other important pro 12:15 a. m. 66' w/150 st	ths of proposed cases work) 6-21-60. LE Posmix	-	4-7%-hil-	
tate names of and expected depths to object  3/4" hole drilled to 76  Ran 5½" 15.5# casing and rementing collar at 3300	DETAl ctive sands; show sign points, and all 60' T.D. d set at 766 ' w/156 ea pressure t	ILS OF WORI  zas, weights, and leng other important pro- 12:15 a. m. 66' w/156 st in Pennin Co test casing t	ths of proposed car posed work) 6-21-60. In Posmix pment @ 11 0 35004 C.	:30 a.m. K. 12:30	6-22-60. P.M 1:	:00 P.
tate names of and expected depths to object of the state	DETAl ctive sands; show sis ing points, and all 60' T.D. d set at 766 w/150 se pressure t	ILS OF WORI  zas, weights, and leng other important pro 12:15 a. ma. 160' w/150 st  E Permix Co test casing to	ths of proposed car posed work) 6-21-60. In Posmix ement @ 11 0 3500# C	:30 a.m. .K. 12:30	6-22-60. P.M l: 6', 7594'-	:00 P.:
tate names of and expected depths to object of the state	DETAl ctive sands; show sis ing points, and all 60' T.D. d set at 766 w/150 se pressure t	ILS OF WORI  zas, weights, and leng other important pro 12:15 a. ma. 160' w/150 st  E Permix Co test casing to	ths of proposed car posed work) 6-21-60. In Posmix ement @ 11 0 3500# C	:30 a.m. .K. 12:30	6-22-60. P.M l: 6', 7594'-	:00 P.:
tate names of and expected depths to object to 3/4" hole drilled to 76 km 5½" 15.5# casing an exmenting collar at 330 prill out D. V. Tool and 6-24-60.	DETA ctive sands; show sizing points, and all 60' T.D. 6 d set at 766 w/150 sa pressure t	ILS OF WORI  zas, weights, and leng other important pro 12:15 a. m. 66' w/150 st ix Permin co test casing t	cths of proposed car 6-21-60. Am Posmix ement @ 11 o 3500f C	:30 a.m. K. 12:30 ', 7573'-8	6-22-60. P.M 1: 6', 7594'- . & 1#/Gai	:00 P.; .7606', I.
tate names of and expected depths to object to 3/4" hole drilled to 76 Ran 5½" 15.5# casing an rementing collar at 330 Drill out D. V. Tool and 6-24-60.	DETA ctive sands; show sizing points, and all 60' T.D. 6 d set at 766 w/150 sa pressure t	ILS OF WORI  zas, weights, and leng other important pro 12:15 a. m. 66' w/150 st ix Permin co test casing t	cths of proposed car 6-21-60. Am Posmix ement @ 11 o 3500f C	:30 a.m. K. 12:30 ', 7573'-8	6-22-60. P.M 1: 6', 7594'- . & 1#/Gai	:00 P.; .7606', I.
tate names of and expected depths to object 3/4" hole drilled to 76 Ran 5½" 15.5% casing as remeating collar at 330 Drill out D. V. Tool and 6-24-60. 6-25-60 Jet Perforate 7612'-30' w/45.P.F	DETA ctive sands; show sis ing points, and all 60' T.D. d set at 766 ' w/150 sa pressure t 7490'-7514' Sand Oil F: 7350'-7412'	ILS OF WORI  zas, weights, and lens other important pro 12:15 a. ma. 66' w/150 st ix Permix co test casing to 7532'-40', rac w/Hallii w/2 S.P.F	this of proposed car 6-21-60. LE PORMIX pment @ 11 0 3509f C. 7544'-68' burten w/3	:30 a.m. K. 12:30 2. 7573'-8 2.000 gal il frac w/	6-22-60. P.M l: 6', 7594'- . @ i#/Gai Hailiburto	:00 P.; .7606', I.
tate names of and expected depths to object 3/4" hole drilled to 76 Ran 5½" 15.5¢ casing as remeating collar at 330 Drill out D. V. Tool and 6-24-60. 6-25-60 Jet Perforate 7612'-30' w/45.P.F 6-29-60 Jet Perforate 76-29-60 Jet	DETA ctive sands; show sign points, and all 60' T.D. 6 d set at 766 i' w/150 sa pressure t 7490'-7514' Sand Oil F: 7350'-7412'	ILS OF WORI  zas, weights, and leng other important pro- 12:15 a. m. 60' w/150 st in Pennin Co test casing to 7532'-40' rac w/Halli w/2 S.P.F	cths of proposed car posed work) 6-21-60. In Posmix pment @ 11 0 3500# C. 7544'-68' burten w/3	:30 a.m., K. 12:30 2. 7573'-8 2. 000 gal 1 frac w/	6-22-60. P.M l: 6', 7594'- . @ 1#/Gai Halliburto	:00 P.; .7606', l.
tate names of and expected depths to object 3/4" hole drilled to 76 Ran 5½" 15.5% casing an rementing collar at 330 for 11 out D.V. Tool and 6-24-60. 6-25-60 Jet Perforate 7612'-30' w/45.P.F 6-29-60 Jet Perforate 76/36,000 gal. & 28,500	DETA ctive sands; show sizing points, and all 60' T.D. d set at 76d w/156 ea pressure t 7490'-7514' Sand Oil F 350'-7412' ded @ 7557'	ILS OF WORI  zas, weights, and leng other important pro- 12:15 a. m. 66' w/150 st in Fermin co test casing to 7532'-40' rac w/Halli w/2 S.P.F	cths of proposed car 6-21-60. An Posmin ement @ 11 to 3500f C. 7544'-68' burten w/3 . Sand of	:30 a.m., K. 12:30 2. 7573'-8 2.000 gal il frac w/l	6-ZZ-60. P.M 1: 6'. 7594' @ 1#/Gai Halliburto: 1-Z-60.	:00 P.; .7606', i. n
tate names of and expected depths to object 3/4" hole drilled to 76 lan 5½" 15.5¢ casing as rementing collar at 330 Drill out D. V. Tool and 6-24-60. 6-25-60 Jet Perforate 7612'-30' w/45.P.F 6-29-60 Jet Perforate 76/36,000 gal. & 28,500 Z" EUE 4.76 tubing lange Total lead and frac oil	DETA ctive sands; show sis ing points, and all 60' T.D. d set at 766 ' w/150 sa pressure t 7490'-7514' Sand Oil F: 7350'-7412' ded @ 7557' purchased	ILS OF WORI  zas, weights, and lens other important pro- 12:15 a. ma. 66' w/150 st ix Permix co test casing to 7532'-40', rac w/Hallii w/2 S.P.F  Well com and used: 2	cths of proposed car 6-21-60. In Posmix ement @ 11 o 3500# C. 7544'-68' burten w/3 . Sand of pleted 4:00 002.14 bbl	:30 a.m. K. 12:30 7. 7573'-8 12.000 gal 11 frac w/1 12.000 gal 13 frac w/1	6-ZZ-60. P.M 1: 6', 7594'- 6', 7594'- 6', 1/Gal falliburto: -2-60. I Paso Na	:00 P.; .7606', i. n .tural (
tate names of and expected depths to object 3/4" hole drilled to 76 lan 5½" 15.5¢ casing as rementing collar at 330 Drill out D. V. Tool and 6-24-60. 6-25-60 Jet Perforate 7612'-30' w/45.P.F 6-29-60 Jet Perforate 76/36,000 gal. & 28,500 Z" EUE 4.76 tubing lange Total lead and frac oil	DETA ctive sands; show sis ing points, and all 60' T.D. d set at 766 ' w/150 sa pressure t 7490'-7514' Sand Oil F: 7350'-7412' ded @ 7557' purchased	ILS OF WORI  zas, weights, and lens other important pro- 12:15 a. ma. 66' w/150 st ix Permix co test casing to 7532'-40', rac w/Hallii w/2 S.P.F  Well com and used: 2	cths of proposed car 6-21-60. In Posmix ement @ 11 o 3500# C. 7544'-68' burten w/3 . Sand of pleted 4:00 002.14 bbl	:30 a.m. K. 12:30 7. 7573'-8 12.000 gal 11 frac w/1 12.000 gal 13 frac w/1	6-ZZ-60. P.M 1: 6', 7594'- 6', 7594'- 6', 1/Gal falliburto: -2-60. I Paso Na	:00 P.; .7606', i. n .tural (
tate names of and expected depths to object 3/4" hole drilled to 76 lan 5½" 15.5¢ casing as rementing collar at 330 Drill out D. V. Tool and 6-24-60. 6-25-60 Jet Perforate 7612'-30' w/45.P.F 6-29-60 Jet Perforate 76/36,000 gal. & 28,500 Z" EUE 4.76 tubing lange Total lead and frac oil	DETA ctive sands; show sis ing points, and all 60' T.D. d set at 766 ' w/150 sa pressure t 7490'-7514' Sand Oil F: 7350'-7412' ded @ 7557' purchased	ILS OF WORI  zas, weights, and lens other important pro- 12:15 a. ma. 66' w/150 st ix Permix co test casing to 7532'-40', rac w/Hallii w/2 S.P.F  Well com and used: 2	cths of proposed car 6-21-60. In Posmix ement @ 11 o 3500# C. 7544'-68' burten w/3 . Sand of pleted 4:00 002.14 bbl	:30 a.m. K. 12:30 7. 7573'-8 12.000 gal 11 frac w/1 12.000 gal 13 frac w/1	6-ZZ-60. P.M 1: 6', 7594'- 6', 7594'- 6', 1/Gal falliburto: -2-60. I Paso Na	:00 P.; .7606', i. n .tural (
tate names of and expected depths to object 3/4" hole drilled to 76 lan 52" 15.5¢ casing an exmenting collar at 330; or object of the collar at 36,000 gal. at 28,500 gal. at 28,5	DETA ctive sands; show sign points, and all of the sand of the sands; show sign points, and all of the sand of the	ILS OF WORI  zas, weights, and lens other important pro- 12:15 a. ma. 66' w/150 st ix Permix co test casing to 7532'-40', rac w/Hallii w/2 S.P.F  Well com and used: 2	cths of proposed car 6-21-60. In Posmix ement @ 11 o 3500# C. 7544'-68' burten w/3 . Sand of pleted 4:00 002.14 bbl	:30 a.m. K. 12:30 7. 7573'-8 12.000 gal 11 frac w/1 12.000 gal 13 frac w/1	6-ZZ-60. P.M 1: 6', 7594'- 6', 7594'- 6', 1/Gal falliburto: -2-60. I Paso Na	:00 P.; .7606', i. n .tural (
tate names of and expected depths to object 3/4" hole drilled to 76 lan 5½" 15.5% casing an exmenting collar at 3300 Drill out D. V. Tool and 6-24-60. 6-25-60 Jet Perforate 7612'-30' w/45.P.F 6-29-60 Jet Perforate 7636,000 gal. & 28.500 Z' EUE 4.7% tubing lam Total load and frac oil Products Co. 7-25-69 ran open flow 1 understand that this plan of work rule 398 F.T. P. Sert Field Company Bert Field	DETA ctive sands; show si- ing points, and all 60' T.D. d set at 766 ' w/150 sa pressure t 7490'-7514' Sand Oil F 350'-7412' ded @ 7557' purchased petantial de petantial de petantial de petantial de	ILS OF WORI  zas, weights, and lens other important pro 12:15 a.m. 60' w/150 st  in Pommin co test casing t  7532'-40' rac w/Hailii w/2 S.P.F  . Well com and used: 2  tiverability in Friday.	cths of proposed car 6-21-60. In Posmix ement @ 11 o 3500# C. 7544'-68' burten w/3 . Sand of pleted 4:00 002.14 bbl	:30 a.m. K. 12:30 7. 7573'-8 12.000 gal 11 frac w/1 12.000 gal 13 frac w/1	6-ZZ-60. P.M 1: 6', 7594'- 6', 7594'- 6', 1/Gal falliburto: -2-60. I Paso Na	:00 P.; .7606', i. n .tural (
tate names of and expected depths to object 3/4" hole drilled to 76 lan 5½" 15.52 casing an exmenting collar at 330 lorill out D. V. Tool and 6-24-60. 6-25-60 Jet Perforate 7612'-30' w/45.P.F 6-29-60 Jet Perforate 7636,000 gal. & 28.500	DETA ctive sands; show si- ing points, and all 60' T.D. d set at 766 ' w/150 sa pressure t 7490'-7514' Sand Oil F 350'-7412' ded @ 7557' purchased petantial de petantial de petantial de petantial de	ILS OF WORI  zas, weights, and lens other important pro 12:15 a.m. 60' w/150 st  in Pommin co test casing t  7532'-40' rac w/Hailii w/2 S.P.F  . Well com and used: 2  tiverability in Friday.	cths of proposed car 6-21-60. In Posmix ement @ 11 o 3500# C. 7544'-68' burten w/3 . Sand of pleted 4:00 002.14 bbl	:30 a.m. K. 12:30 7. 7573'-8 12.000 gal 11 frac w/1 12.000 gal 13 frac w/1	6-ZZ-60. P.M 1: 6', 7594'- 6', 7594'- 6', 1/Gal falliburto: -2-60. I Paso Na	:00 P.; .7606', i. n .tural (
tate names of and expected depths to object 3/4" hole drilled to 76 lan 5½" 15.52 casing an exmenting collar at 330 lorill out D. V. Tool and 6-24-60. 6-25-60 Jet Perforate 7612'-30' w/45.P.F 6-29-60 Jet Perforate 7636,000 gal. & 28.500	DETA ctive sands; show si- ing points, and all 60' T.D. d set at 766 ' w/150 sa pressure t 7490'-7514' Sand Oil F 350'-7412' ded @ 7557' purchased petantial de petantial de petantial de petantial de	ILS OF WORI  zas, weights, and lens other important pro 12:15 a.m. 60' w/150 st  in Pommin co test casing t  7532'-40' rac w/Hailii w/2 S.P.F  . Well com and used: 2  tiverability in Friday.	cths of proposed car 6-21-60. In Posmix ement @ 11 o 3500# C. 7544'-68' burten w/3 . Sand of pleted 4:00 002.14 bbl	:30 a.m. K. 12:30 7. 7573'-8 12.000 gal 11 frac w/1 12.000 gal 13 frac w/1	6-ZZ-60. P.M 1: 6', 7594'- 6', 7594'- 6', 1/Gal falliburto: -2-60. I Paso Na	:00 P.; .7606', i. n .tural (
tate names of and expected depths to object 3/4" hole drilled to 76 lan 52" 15.5¢ casing an exmenting collar at 330; original out D. V. Tool and 6-24-60. 6-25-60 Jet Perforate 7612'-30' w/45.P.F 6-29-60 Jet Perforate 7612'-30' w/45.P.F 6-29-60 Jet Perforate 7612'-40 gal. & 28.500 2" EUE 4.7¢ tubing lan Total lead and frac oil Products Co. 7-24-60 ran open flow I understand that this plan of work rate 398 F. T. Products Co. Bert Field Address 1211 Fidelity 1	DETA ctive sands; show si- ing points, and all 60' T.D. d set at 766 ' w/150 sa pressure t 7490'-7514' Sand Oil F 350'-7412' ded @ 7557' purchased petantial de petantial de petantial de petantial de	ILS OF WORI  zas, weights, and lens other important pro 12:15 a.m. 60' w/150 st  in Pommin co test casing t  7532'-40' rac w/Hailii w/2 S.P.F  . Well com and used: 2  tiverability in Friday.	cths of proposed car 6-21-60. In Posmix ement @ 11 o 3500# C. 7544'-68' burten w/3 . Sand of pleted 4:00 002.14 bbl	:30 a.m. K. 12:30 7. 7573'-8 12.000 gal 11 frac w/1 12.000 gal 13 frac w/1	6-ZZ-60. P.M 1: 6', 7594'- 6', 7594'- 6', 1/Gal falliburto: -2-60. I Paso Na	:00 P.; .7606', i. n .tural (
tate names of and expected depths to object 3/4" hole drilled to 76 lan 5½" 15.5% casing an exmenting collar at 3300 Drill out D. V. Tool and 6-24-60. 6-25-60 Jet Perforate 7612'-30' w/45.P.F 6-29-60 Jet Perforate 7636,000 gal. & 28.500 Z' EUE 4.7% tubing lam Total load and frac oil Products Co. 7-25-69 ran open flow 1 understand that this plan of work rule 398 F.T. P. Sert Field Company Bert Field	DETA ctive sands; show si- ing points, and all 60' T.D. d set at 766 ' w/150 sa pressure t 7490'-7514' Sand Oil F 350'-7412' ded @ 7557' purchased petantial de petantial de petantial de petantial de	ILS OF WORI  zas, weights, and lens other important pro 12:15 a.m. 60' w/150 st  in Pommin co test casing t  7532'-40' rac w/Hailii w/2 S.P.F  . Well com and used: 2  tiverability in Friday.	cths of proposed car 6-21-60. In Posmix ement @ 11 o 3500# C. 7544'-68' burten w/3 . Sand of pleted 4:00 002.14 bbl	:30 a.m.  K. 12:30  7573'-8  12.000 gal  1 frac w/  1 f	P.M 1: 6', 7594'- 6	:00 P.; .7606', i. n .tural (
tate names of and expected depths to object 3/4" hole drilled to 76 lan 52" 15.5¢ casing an exmenting collar at 330; original out D. V. Tool and 6-24-60. 6-25-60 Jet Perforate 7612'-30' w/45.P.F 6-29-60 Jet Perforate 7612'-30' w/45.P.F 6-29-60 Jet Perforate 7612'-40 gal. & 28.500 2" EUE 4.7¢ tubing lan Total lead and frac oil Products Co. 7-24-60 ran open flow I understand that this plan of work rate 398 F. T. Products Co. Bert Field Address 1211 Fidelity 1	DETA ctive sands; show si- ing points, and all 60' T.D. d set at 766 ' w/150 sa pressure t 7490'-7514' Sand Oil F 350'-7412' ded @ 7557' purchased petantial de petantial de petantial de petantial de	ILS OF WORI  zas, weights, and lens other important pro 12:15 a.m. 60' w/150 st  in Pommin co test casing t  7532'-40' rac w/Hailii w/2 S.P.F  . Well com and used: 2  tiverability in Friday.	cths of proposed car 6-21-60. In Posmix ement @ 11 o 3500# C. 7544'-68' burten w/3 . Sand of pleted 4:00 002.14 bbl	:30 a.m. K. 12:30 7. 7573'-8 12.000 gal 11 frac w/1 12.000 gal 13 frac w/1	P.M 1: 6', 7594'- 6	:00 P.; .7606', i. n .tural (
Address 1211 Fidelity to African special and specia	DETA ctive sands; show si- ing points, and all 60' T.D. d set at 766 ' w/150 sa pressure t 7490'-7514' Sand Oil F 350'-7412' ded @ 7557' purchased petantial de petantial de petantial de petantial de	ILS OF WORI  zas, weights, and lens other important pro 12:15 a.m. 60' w/150 st  in Pommin co test casing t  7532'-40' rac w/Hailii w/2 S.P.F  . Well com and used: 2  tiverability in Friday.	cths of proposed car 6-21-60. In Posmix ement @ 11 o 3500# C. 7544'-68' burten w/3 . Sand of pleted 4:00 002.14 bbl	:30 a.m.  K. 12:30  7573'-8  12.000 gal  1 frac w/  1 f	P.M 1: 6', 7594'- 6	:00 P.; .7606', i. n .tural (

• .