Form 3160-5 (August 1999)

UNITED STATES DETARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

DUKEAU OI	LAND	MININITALIGNATION	

SUNDRY NOTICES AND REPORTS ON WELLS

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

5.	Lease Serial No.
	NMSF080672

			- ·	- ·
6.	If Indian.	Allottee or	lribe	Name

Do not use thi abandoned wel	6. If Indian, Allotte	6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRII		7. If Unit or CA/Agreement, Name and/or No. NMNM78408C		
1. Type of Well			8. Well Name and SJ 27-4 80	No.
☐ Oil Well ☐ Gas Well ☐ Oth 2. Name of Operator BURLINGTON RESOURCES	Contact: Pl	EGGY COLE AUG Mail: pcole@bi-inc.com	9. API Well No. 30-039-2082	2-00-S1
3a. Address P O BOX 4289 FARMINGTON, NM 87499		3b. Phone No(include area code Ph: 505.326,9727 Fx: 505.326,9781	10. Field and Pool TAPACITO	, or Exploratory
4. Location of Well (Footage, Sec., 7	C., R., M., or Survey Description)	No.	11. County or Pari	sh, and State
Sec 24 T27N R4W SWSE 100 36.55421 N Lat, 107.19940 W	00FSL 1760FEL / Lon		RIO ARRIBA	COUNTY, NM
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE NATURE OF	NOTICE, REPORT, OR OTI	HER DATA
TYPE OF SUBMISSION		ТҮРЕ С	OF ACTION	
CY.	☐ Acidize	☐ Deepen	☐ Production (Start/Resume)) ☐ Water Shut-Off
☐ Notice of Intent	☐ Alter Casing	☐ Fracture Treat	□ Reclamation	■ Well Integrity
■ Subsequent Report	☐ Casing Repair	□ New Construction	☐ Recomplete	☐ Other
☐ Final Abandonment Notice	☐ Change Plans	Plug and Abandon	☐ Temporarily Abandon	
	☐ Convert to Injection	☐ Plug Back	☐ Water Disposal	
If the proposed of Confipieta Op If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved testing has been completed. Final A determined that the site is ready for 17-23-02 MIRU. ND WH. NU I 4122'. TOOH. TIH w/2 7/8" CITIH, tag CIBP @ 4010'. Circ injection. Plug #1: pump 5 sx Pictured Cliffs perfs. TOOH to 7-24-02 TIH, tag TOC @ 396 TOOH. TIH, load hole w/2 bb pump 135 sx Type II cmt beloinside csg above cmt retainer to change plans from Tod Ha 7-25-02 TIH, tag TOC @ 345 TOOH. TIH. Load hole w/2 bb TOOH. TIH. Load hole w/2 bb	ork will be performed or provide the operations. If the operation result bandonment Notices shall be filed final inspection.) BOP. TIH w/2 7/8" gauge ristible, set @ 4010'. (Change role clean w/25 bbl wtr. Atterpoole	ne Bond No. on file with BLM/B lts in a multiple completion or re I only after all requirements, including to 3010'. TOOH. TIH w/of plans approved by Todempt to PT 2 7/8" csg, faile csg on top of CIBP @ 4010 s cmt w/15 bbl wtr. TOOH. 4'. TOOH. TIH w/cmt retain tsg, failed. Establish injection in the complex of the compl	A. Required subsequent reports sha completion in a new interval, a Form uding reclamation, have been comple 1 3/4" tbg broach to Haanes, BLM). TOOH. d. Establish ' to cover WOC. SDON. ner, set @ 3905'. on. Plug #2: np 15 sx Type II cmt erbal approval	3160-4 shall be filed once
14. I hereby certify that the foregoing i	Electronic Submission #1		t to the Farmington 08/20/2002 (02SXM0139S)	
Name (Printed/Typed) PEGGY (COLE	Title REGU	ILATORY ADMINISTRATOR	
Signature (Electronic	Submission)	Date 08/19.	/2002	
	THIS SPACE FO	R FEDERAL OR STATE	OFFICE USE	
_Approved ByACC	CEPTED		PHEN MASON FROLEUM ENGINEER DA	ate 08/20/2002
Conditions of approval, if any, are attach certify that the applicant holds legal or exwhich would entitle the applicant to conditions.	quitable title to those rights in the	not warrant or subject lease Office Far	mington	

Additional data for EC transaction #13670 that would not fit on the form

32. Additional remarks, continued

pump 35 sx Type II cmt outside csg below cmt retainer @ 2310-2410'. Pump 5 sx Type II cmt inside csg above cmt retainer to cover Nacimiemto interval. TOOH. WOC. TIH, tag TOC @ 2200'. TOOH. TIH, perf 3 sqz holes @ 177'. Establish circ down 2 7/8" csg & out bradenhead valve w/13 bbl wtr. Plug #4: pump 111 sx Type II cmt down 2 7/8" csg & out bradenhead valve. Circ 2 bbl cmt to surface. WOC. ND BOP. Cut off WH. Cmt fell 8' in annulus & 200' in 2 7/8" csg. Pump 5 sx Type II cmt to fill 2 7/8" csg & annulus. Install dry hole marker w/5 sx Type II cmt. SDON. 7-26-02 RD. Rig released.

Well plugged and abandoned 7-25-02