

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF079367-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL ☐ GAS ☒ OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

P. O. Box 990, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1780'N, 1020'W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

6574' GL

7. UNIT AGREEMENT NAME

San Juan 28-6 Unit

8. FARM OR LEASE NAME

San Juan 28-6 Unit

9. WELL NO.

200

10. FIELD AND POOL, OR WILDCAT

South Blanco PC

11. SEC., T., R., M., OR B.L.K. AND
SURVEY OR AREASec. 25, T-27-N, R-6-W
N.M.P.M.

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐WATER SHUT-OFF ☒FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-16-74 TD 3337'. Ran 100 joints 2 7/8", 6.4 and 6.5#, J-55 and K-55 production casing, 3327' set at 3337'. Baffle set at 3327'. Cemented with 360 cu. ft. cement. WOC 18 hours. Top of cement at 1600'.

12-10-74 Tested casing to 4000#--OK.
PBSD 3326'. Perf'd, 3240-60', 3270-86', 3294-3302' with 8 shots per zone. Frac'd with 58,000#, 10/20 sand and 58,716 gallons treated water. Dropped 2 sets of 8 balls each. Flushed with 798 gallons water.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. G. Busco

TITLE

Drilling Clerk

DATE

December 13, 1974

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: