

A - PLUS WELL SERVICE, INC.

P.O. BOX 1979
FARMINGTON, NM 87499
505-325-2627 • FAX: 505-325-1211

Conoco, Inc.

May 3, 1996

San Juan 28-7 Unit #196 (PC)

860' FSL, 1840' FEL, Sec. 10, T-27-N, R-7-W

Rio Arriba County, NM

SF - 078972

Plug & Abandonment Report

Cementing Summary:

Plug #1 mix and pump 90 sxs Class B cement down 2-7/8" casing; displace cement to 500' covering Pictured Cliffs perforations, Fruitland, Kirtland, Ojo Alamo and Nacimiento tops.

Plug #2 with 83 sxs Class B cement from 176' to surface, circulate good cement out bradenhead.

Plugging Summary:

Notified BLM on 4/30/96

4-30-96 Road cement equipment to location. RU cement equipment. Layout relief lines to pit. Pump 22 bbls water 3-1/2 bpm at 200#, no blow out bradenhead. Drop 25 RCN balls; followed with 19 bbls water at 3-1/2 bpm; pressure increased to 500#. Pump additional 3 bbls water, 3-1/2 bpm at 500#, no blow out bradenhead. Plug #1 mix and pump 90 sxs Class B cement down 2-7/8" casing; displace cement to 500' covering Pictured Cliffs perforations, Fruitland, Kirtland, Ojo Alamo and Nacimiento tops. Shut in well and WOC.

5-2-96 Road cement equipment to location. RU cement equipment. RU A-Plus wireline truck. RIH and tag cement at 720'. Perforate 2 squeeze holes at 176'. Establish circulation out bradenhead with 21 bbls water. Plug #2 with 83 sxs Class B cement from 176' to surface, circulate good cement out bradenhead. Shut in well and WOC. Dig out wellhead. Open up well. Cut off wellhead. Mix 20 sxs Class B cement and install P&A marker.
J. Ruybalid, BLM, was on location 5/2/96.