Form 9-331 (May 1963)

UNITED STATES SUBMIT IN TRIPLICATE* DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

	SF0.806.73 G. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY (Do not use this form for Use "			
1.		7. UNIT AGREEMENT NAME	
WELL GAS WELL	OTHER	San Juan 27-4 Unit	
2. NAME OF OPERATOR	8. FARM OR LEASE NAME		
El Paso Natural	San Juan 27-4 Unit		
3. ADDRESS OF OPERATOR	9. WELL, NO.		
P. O. Box 990, F	armington, New Mexico 87401	125 (PM)	
4. LOCATION OF WELL (Report 1 See also space 17 below.) At surface	Undes. PC Blanco Mesa Verde		
1840'N, 1	850'E	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
Parties of the second		Sec. 8, T-27-N, R-4-W N.M.P.M.	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE	
	6938' GL	Rio Arriba New Mexico	
16. Ch	teck Appropriate Box To Indicate Nature of Notice, Report,	or Other Data	
NOTICE	OF INTENTION TO:	SSEQUENT REPORT OF;	

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:					
TEST WATER SHUT-OFF		FULL OR ALTER CASING		WATER SHUT-OFF	X	REPAIRING WELL	
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT	<u>X</u>	ALTERING CASING	
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING		ABANDONMENT*	
REPAIR WELL		CHANGE PLANS	\	(Other)			l
(Other)				(Note: Report rest Completion or Reco	ults of multiple mpletion Report	completion on Wel t and Log form.)	1

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *
 - 07-29-76 TD 4184". Ran 104 joints 7", 20#, KS intermediate casing, 4172' set at 4184'. Cemented with 253 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 3090'.
 - 08-02-76 TD 6400'. Ran 75 joints 4 1/2", 10.5#, KS casing liner, 2382' set 4018-6400'. Float collar set at 6383'. Cemented with 415 cu. ft. cement. WOC 18 hours.
 - PBTD 6383'. Tested casing to 4000#, OK. Perf'd PC 3841',3855',3859',3880', 3885',3890',3910',3915',3920' with 1 shot per zone. Frac'd with 60,000#--10/20 sand and 64,176 gallons water. No ball sets dropped. Flushed with 7098 gallons water. Perf'd MV 5525',5541',5583',5593',5607',5621',5629',5639',5649',6023',6028',6033',6045',6049',6099',6106',6117',6130',6151',6171',6219',6265',6294',6331',6361' with 1 shot per zone. Frac'd with 60,000#--20/40 sand and 60,816 gallons water. No ball sets dropped. Flushed with 8484 gallons water.

18. I hereby certify that the foregoing is true and correct	OCT 4 100	
SIGNED D. Brisco	TITL DOTTI Ting Clerk	DATE September 24, 1976
(This space for Federal or State office use)		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE