form	9-331
(May	1963)

16.

UNITED STATES SUBMIT IN TRIPLICATE* DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side)

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

GEOLOGICAL SURVEY

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

-NMO 3560 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Use "APPLICA	TION FOR PERMIT—" for suc	h proposals.)		
•			7. UNIT AGREEMENT	NAME
WELL GAS WELL OTHER			San Juan 28	-7 Unit
. NAME OF OPERATOR			8. FARM OR LEASE	NAME
El Paso Natural Gas Com	pany		San Juan 28	3-7 Unit
. ADDRESS OF OPERATOR			9. WELL NO.	
P. O. Box 990, Farmingt	on, NM 87401		101	
 LOCATION OF WELL (Report location cl See also space 17 below.) At surface 	early and in accordance with a	131	Basin Dakot	
1795'S, 970'W		JUL SIST COM	7 1	
4. PERMIT NO.	15. ELEVATIONS (Show whether	r DF, RT, GR,	12. COUNTY OR PAR	ISH 13. STATE
	6636' GL		Rio Arriba	New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:			
					<u> </u>
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL		CHANGE PLANS		(Other)	
(Other)				(Norn: Report results of mu Completion or Recompletion	Report and Log form.)

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.).
 - TD 7482'. Ran 227 joints 4 1/2", 10.5 and 11.6#, K-55 production casing, 7473' set at 7482'. Float collar set at 7465'. Stage tools set at 06 - 27 - 753049' and 5433'. Cemented first stage with 346 cu. ft. cement; second stage with 419 cu. ft. cement; third stage with 524 cu. ft. cement. WOC 18 hours. Top of cement at 1950'.
 - PBTD 7465'. Tested casing to 4000#--OK. Perf'd 7216', 7232', 7240', 07-15-75 7282', 7298', 7331', 7357', 7370', 7384', 7395', 7416' with 1 shot per zone. Frac'd with 90,000#--40/60 sand and 98,994 gallons treated water. Dropped no balls. Flushed with 4788 gallons water.

SIGNED SIGNED SIGNED	TITLE Drilling Clerk	DATE July 23, 1975
(This space for Federal or State office use)		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE .