STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reparting packer leskage tests a Southeast New Mario

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

| | In Souther | ast New Mexico | MONITIAM | | | | | | |
|----------------------|--|--|-----------------------|--------------------------|-----------------------|------------------|-----------------------------|--------------------------------|--|
| erator | National Cooperative Refinery Association | | | Lease | Cand | andado | | Well 18 | |
| _ | | I Sec. 25 | Twp26N | Rge | 71:1 | | County | Rio Arriba | |
| wen. | <u> </u> | NAME OF RESERV | | TYPE OF P | ROD. | METHOD OF | | PROD. MEDIUM (Tbg. or Ceg.) | |
| Jpper npletion | Pio | Pictured Cliffs Gas | | | Flow | | Tbg | | |
| ower optation | Cha | acra | | Gas | | Flow | | Tba | |
| | | | | OW SHUT-IN P | | TA | I Grahilles | t2 (Yes or No) | |
| pper nptetion | Hour, date shul-in Length of time shul-in 11/27/91 72 ht | | | hrs | rs 310 | | Stabilized? (Yes or No) Yes | | |
| ower nptetion | Hour, dale | Hour, date shul-in Length of time shul-in 72 hrs | | | Si press. psig 260 | | Stabilize | Stabilized? (Yes or No) Yes | |
| | | | | FLOW TEST | | | . laur | | |
| menced | et (hour, di | nte)# 7:09 11/ | | | Zone producti | ng (Upper or Low | •r⊧ Lower | | |
| TIME (hour, date) | | LAPSED TIME SINCE* | PRES Upper Completion | SURE Lower Completion | PROD. ZON TEMP. | E | | REMARKS | |
| :00 1/30 | | 0 | 310 | 260 | | | 4 | | |
| :00 1/30 | p.m. | 8 | 310 | 180 | | | -1 | | |
| 2/01 | a.m. | 24 | 310 | 180 | | | | , | |
| | | | | | | | | | |
| | | - | | | | | | | |
| | | | | | | | | | |
| ductio | on rate o | luting test | <u></u> | | | | | | |
| | | BOI | D based on | Bbls. ii | n H | ours. | G12v | GOR | |
| s: | 1 | | | PD; Tested thru | (Orifice or N | deter): | Meter | | |
| | | | MID-TI | ST SHUT-IN P | RESSURE DA | ·ΤΛ | | | |
| | Hour, date | shut-in | Length of time shu | ıt-in | Si prese, peig | | Stabilized? (Yes or No) | | |
| Jpper npielion | Hour, date shut-in Length of time shul | | | SI press. pelg | | | Stabilized? (Yes or No) | | |

GIL CON. :

(Continue on reverse side)

FLOW TEST NO. 2

| Commenced at (hour, date) 中半 / 100 12/04/91 | | | | Zone producing (Upper or Lower): UDDEY | | | |
|---|-------------------------|------------------|------------------|--|-------|--|--|
| TIME | LAPSED TIME SINCE ** | PRESSURE | | PROD. ZONE | | | |
| (hour, date) | | Upper Completion | Lower Completion | TEMP. | REMA | AKS | |
| 7:00 a.m. 12/04/91 | 0 | 310 | 260 | | | | |
| 4:00 p.m. 12/04/91 | ٥ | 185 | 260 | | | | |
| 7:00 a.m. 12/05/91 | 24 | 185 | 260 | | | | |
| | | | | | | | |
| | | | | | | <u> </u> | |
| | | | | JECTO DE LEGICIO | | | |
| Production rate du | iring test | | | | | | |
| Oil:0 | ВОР | D based on | Bbls. in | Hours | Grav | GOR | |
| Gas:46 | | MCF | PD: Tested thru | Orifice or Meter): _ | Meter | | |
| | leak detec | | | · · · · · · · · · · · · · · · · · · · | | ······································ | |

| I hereby certify that the information h | erein contained is true and | l complete to the best of r | ny knowledge. |
|---|-----------------------------|-----------------------------|---------------|
| 17 N A 9 10.57 | 7 | | |

| Approved 17:18 U 3 1332 19 19 New Mexico Oil Conservation Division | | Operator | NCRA | | |
|--|------------------------------------|-----------------------|------|--|--|
| By | Original Signed by CHARLES UNCLSON | By Production Manager | | | |
| | DEPUTY OIL & GAS INSPECTOR DIST #4 | ***** | | | |

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

Date _

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Title

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

12 - 30 - 91

- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Azec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packet Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).