

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 079527A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Champlin

9. WELL NO.

#3A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 35, T27N, R4W NM

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

1.

OIL ☐ GAS ☒
WELL WELL OTHER

2. NAME OF OPERATOR

Consolidated Oil & Gas, Inc.

3. ADDRESS OF OPERATOR

1860 Lincoln Street, Denver, Colorado 80295

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1790' FNL & 1660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7057' Gr.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Case & Cement

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-17-78 Drilled 8 3/4" hole to 4185'. Ran 4157' of 7" 23# K-55 ST&C Rge 3 csg. and set @ 4169' K.B. Cemented w/150 sx 65-35 poz and 100 sx C1 "B" w/2% Cacl₂ w 1/2#/sx Celloflake.
P.D. 11:00 a.m. WOC 12 hrs. Top of cement by temp. survey 2650.
Pressure test csg. to 1000' psi.

1-20-78 Air drill 6 1/2" hole - 6400' K.B. Ran ID-Gamma Ray & FDC Log. Ran 2251' 4 1/2" 10.50# K-55 ST&C liner & set @ 6310' K.B. FC 6266'. Top of liner 4059' K.B. Cemented w/275 sx 50-50 poz 4% gel & 10# fine Gilsonite per sx. Plug Down 9:15 p.m.

WO Completion Rig.

18. I hereby certify that the foregoing is true and correct

SIGNED

O.B. Whitenburg

TITLE

Sr. Drlg. Engineer

DATE

1-24-78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY
DENVER, COLO.