TO STATE OF

ميداد أبير أأباد

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

- paparagrafica **samangan katal**ah mengapanan pahaga berpada ada 1886-an ar depakan ipaka darah ada da

5. LE.	ASE	۲.	J:	<u>.</u>	ن پورن	<i>3</i>	-		
SF	07849	6	3	1	E		:	ž	3

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME					
0.0000.000						
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME					
(Do not use this form for proposals to drill or to deepen or plug back to a different	San Juan 28-7 Unit					
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME					
1. oil gas 🕞	San Juan 28-7 Unit					
well well other	9. WELL NO.					
2. NAME OF OPERATOR	260 불통하다 된 박실로					
EL PASO NATURAL GAS CO.	10. FIELD OR WILDCAT NAME TO SEE					
3. ADDRESS OF OPERATOR	Basin Dakota = = =					
BOX 289, FARMINGTON, NEW MEXICO	11. SEC., T., R., M., OR BLK. AND SURVEY OR					
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 5, T-27-N, R-7-W					
below.)	NMPM seed to the s					
AT SURFACE: 890'N, 1780'E	12. COUNTY OR PARISH 13. STATE					
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Rio Arriba New Mexico					
AT TOTAL DEPTH:	14. API NO. 1984 2 3 3 4 4 4					
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,						
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)					
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6696 GL 5 8 7 7 8 8 8 8 8					
TEST WATER SHUT-OFF	변출학원 및 권실했음					
FRACTURE TREAT	물로 가는 물로 살림하는 그를 살림하는 그를 살림하는 것이 되었다.					
SHOOT OR ACIDIZE	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그					
REPAIR WELL	(NOTE: Report results of multiple completion or zone					
PULL OR ALTER CASING	change on Form 9–330.)					
MULTIPLE COMPLETE						
ABANDON*						
(other)						
	<u> </u>					
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is d	e all pertinent details, and give pertinent dates, irectionally drilled give subsurface locations and					
measured and true vertical depths for all markers and zones pertiner	nt to this work.)*					
12/13/78: Spudded well. Drilled surface ho	ole a la l					
12/15/70. Spauded well. Diffied Saliace he	17. a 44.44 a 44.14					
12/14/78: Ran 5 joints 9 5/8", #36#, K-55 s	surface casing 200' set					
at 213'. Cemented with 224 cu. ft. cement.	Circulated to surface					
WOC 12 hours; held 600#/30 minutes.						
mod 12 hours, here over/so mindoes.						
	TO THE PERSON OF					
	THE SECOND PROPERTY OF THE PRO					
	THE STATE OF THE S					
	n and the second					

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

Set @ Ft. Set

*See Instructions on Reverse Side