

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1840'N, 870'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF 079364

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Rincon Unit

8. FARM OR LEASE NAME
Rincon Unit

9. WELL NO.
135 A

10. FIELD OR WILDCAT NAME
So. Blanco PC. & Blanco MV

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 29, T-27-N, R-6-W
N.M.P.M.

12. COUNTY OR PARISH
Rio Arriba

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6664' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-29-79: PBD 5907'. Tested casing to 3500#, OK. Perfed P.L. 5384, 5391, 5398, 5424, 5440, 5446, 5452, 5458, 5464, 5470, 5486, 5491, 5496, 5508, 5516, 5528, 5548, 5567, 5574, 5622, 5661, 5676, 5691, 5701, 5761, 5804' W/1 SPZ. Fraced w/ 88,500# 20/40 sand, 177,000 gal. wtr. Flushed w/7350 gal. wtr. Perfed C.H. & Men. 4930, 4935, 4940, 4945, 4950, 5088, 5208, 5213, 5218, 5266, 5270, 5274, 5324' W/1 SPZ. Fraced w/ 32,000# 20/40 sand, 64,000 gal. wtr. Flushed w/7000 gal. water.

10-30-79: Perfed 3174-3190, 3212-3236' W/16 SPZ. Fraced w/ 40,000# 10/20 sand, 45,500 gal. wtr. Dropped 1 set of 16 balls each. Flushed w/5500 gal. wtr.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____

18. I hereby certify that the foregoing is true and correct

SIGNED J. P. Trues TITLE Drilling Clerk DATE October 31, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side