

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington,

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 850'N, 1575'W

AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☒
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF 080673

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
San Juan 27-4 Unit

8. FARM OR LEASE NAME
San Juan 27-4 Unit

9. WELL NO.
124A (PM)

10. FIELD OR WILDCAT NAME
Tapacito PC & Blanco MV

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 8, T-27-N, R-4-W
NMMP

12. COUNTY OR PARISH | 13. STATE
Rio Arriba | New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6771' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL CON. COM.
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-7-80: PBTD 6306'. Tested casing to 3500#, OK. Perfed Point Lookout: 5836, 5842, 5848, 5860, 5866, 5914, 5949, 5955, 5961, 6099, 6126, 6136, 6154, 6225, 6233' W/1 SPZ. Fraced w/ 34,500# 20/40 sand, 69,000 gal. wtr. Flushed w/ 7812 gal. wtr.

Perfed Cliff House & Menefee:

5345, 5365, 5406, 5421, 5426, 5444, 5458, 5466, 5472, 5635, 5642, 5648, 5665, 5669, 5683, 5689, 5695, 5767, 5775' W/1 SPZ. Fraced w/ 49,500# 20/40 sand, 99,000 gal. wtr. Flushed w/ 7518 gal. wtr.

Perfed Pictured Cliffs 3661-74, 3680-90, 3698-3710, 3726-46' W/12 SPZ. Fraced w/ 56,000# 10/20 sand, 66,000 gal. wtr. Flushed w/ 6216 gal.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

wtr. Dropped 3 sets of 12 balls each.

18. I hereby certify that the foregoing is true and correct

SIGNED D. D. Susco TITLE Drilling Clerk DATE November 12, 1980

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

NMOCC