

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Sundry Notices and Reports on Wells

1. Type of Well Gas	5. Lease Number NM-067988
2. Name of Operator Little Oil & Gas, Inc., c/o Joe Elledge	6. If Indian, All. or Tribe Name
3. Address & Phone No. of Operator P. O. Box 111, Farmington, NM 87499	7. Unit Agreement Name
Location of Well, Footage, Sec., T, R, M 1818' FSL and 790' FEL, Sec. 17, T-26-N, R-7-W,	8. Well Name & Number Foster #1
	9. API Well No. 30-039-70239 22874
	10. Field and Pool So. Blanco PC
	11. County & State Rio Arriba County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other -
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

Little Oil & Gas, Inc. plugged and abandoned this well on February 11, 1999 per the following:

2-11-99 Safety Meeting. Road cement equipment to location for rigless P&A. Open up well, no pressure on casing or bradenhead. ND wellhead and install cementing valve. Pump 30 bbls water down casing and establish rate 3 bpm at 300-400#. No bradenhead blow or indication of casing leak. Plug #1 mix 103 sxs Class B cement and pump down 2-7/8" casing to 2776' to fill Pictured Cliffs perforations and to cover Fruitland, Kirtland, Ojo Alamo tops and surface casing shoe, did not displace. Shut in well with double valve and WOC 2 hours. Dig out wellhead and cut off. Found cement down 20' in 2-7/8" casing and down 60' in 7" annulus. Mix 20 sxs Class B cement, fill casing and annulus; then install P&A marker. RD cement equipment and move off location. K. Schneider, BLM, was on location.

14. I hereby certify that the foregoing is true and correct.

Signed Joe Elledge Title Agent Date 2/16/99

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

FEB 24 1999

NMOC

FARMINGTON FIELD OFFICE
BY _____