

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

RECEIVED
JUN - 8 1994

2. Name of Operator
MERIDIAN OIL

OIL CON. DIV.
DIST. 3

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
990' FNL, 990' FWL Sec. 13, T-27-N, R-3-W, NMPM

5. Lease Number
Jic. Contract 89
6. If Indian, All. or
Tribe Name
Jicarilla Apache
7. Unit Agreement Name
8. Well Name & Number
Jicarilla 89 #6
9. API Well No.
30-039-
10. Field and Pool
Blanco MV/Gavilan PC
11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input checked="" type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injectio
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

05-18-94 MOL&RU. Blow down & kill well. ND WH. NU BOP. TOOH w/tbg. Ran gge ring to 6053'. Set RBP @ 3830'. Load hole w/wtr. Ran CBL-GR-CCL 3830-0'. Excellent cmt to 3420' w/good to spotty cmt to 400'. Set pkr @ 65'. PT csg 3000#/15 min, ok. Dump 2 sx sand on RPB @ 3830'. Spot 790 gal acid. TOOH to 2000'. Unload w/air. Perf 3736-70' w/2 spf. Ran pressure bomb for 6 hr.
05-19-94 TOOH w/bomb. Set pkr @ 3698'. Spot 2000 gal acid. Frac lower Pictured Cliffs 3736-70' w/122,674# 20/40 sand, x-link gel, N2 and foam. Flow back frac.
05-20-94 Flow back. CO and flow well.
05-21-94 Set pkr @ 65'. PT 3000#/15 min, ok. Spot 250 gal acid 3640-3500'. Pull up to 1600'. Perf 3523-3644' w/2 spf. Set pkr @ 3478'. Ran pressure bomb to 3550'. Pull bomb. Spot 3750 gal acid.
05-22-94 Frac w/234,000# 20/40 sand, x-link gel and N2 foam. Flow back after frac.
05-23/26 Flow well and CO.
05-27-94 Ran after frac log 3830-3200'. Ran 2 3/8", 4.7#, J-55 tbg landed @ 3770'. ND BOP. NU WH. Released rig.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 5/27/94

(This space for Federal or State Office use)
APPROVED BY Joseph Garamillo Title Assistant and Mineral Resources Date JUN 7 1994
CONDITION OF APPROVAL, if any: