

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
2. NAME OF OPERATOR  
El Paso Natural Gas Company  
3. ADDRESS OF OPERATOR  
PO BOX 4289, Farmington, NM 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 940'N, 920'W  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:  
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:


☐  
☒  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
SF 080672  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
San Juan 27-4 Unit  
8. FARM OR LEASE NAME  
San Juan 27-4 Unit  
9. WELL NO.  
32  
10. FIELD OR WILDCAT NAME  
Blanco Mesa Verde  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 23, T-27-N, R-4-W, NMPM  
12. COUNTY OR PARISH  
Rio Arriba  
13. STATE  
NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6812' KB

RECEIVED

SEP 28 1982

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N.M.



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9-24-82 PBSD 6377'. Tested casing to 4000#, OK. Perf'd 5948', 5954', 5960', 5966', 5972', 5978', 6008', 6027', 6035', 6048', 6060', 6066', 6086', 6106', 6166', 6180', 6207', 6222', 6267', 6303', 6315' with 1 spz. Fraced with 60,000# 20/40 sand and 149,736 gallons treated water. Flushed with 7938 gallons water. Perf'd 5538', 5546', 5566', 5571', 5590', 5597', 5604', 5849' with 1 spz. Fraced with 18,000# 20/40 sand and 41,796 gallons treated water. Flushed with 15,330 gallons water.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. B. Lico TITLE Drilling Clerk DATE September 27, 1982

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

SEP 30 1982