

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1820'N, 960'E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED

SEP 02 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE

SF 079491A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 27-5 Unit

8. FARM OR LEASE NAME

San Juan 27-5 Unit

9. WELL NO.

199

10. FIELD OR WILDCAT NAME

Tapacito P. C.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 10, T-27-N, R-5-W

N.M.P.M.

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

1302' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-11-82 - Spudded well, drilled surface hole, ran 5 joints 8 5/8", 24.0#, K-55 surface casing (206') set at 218' w/165 cu. ft. cement circulated to surface. W.O.C. 12 hours. Held 600#/30 Minutes.

8-13-82 drilled to 390', lost circulation. Squeeze cemented w/118 cu. ft. cement. W.O.C. 4 hours. Cleaned out to 330', lost circulation. Squeeze cemented w/94 cu. ft. cement. W.O.C. 4 hours. Drilled out to 400', lost circulation. Squeeze cemented w/83 cu. ft. cement. w.o.c. 4 hours.

8-14-82 Resumed drilling operation.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

A. B. Dices

TITLE

Drilling Clerk

DATE

September 2, 1982

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

SEP 03 1982

FARMINGTON, N.M.

BY

Sm

*See Instructions on Reverse Side

NMOCC