Form Approved.
Budget Bureau No. 42-R1424

Dec. 1973	bouget bureau no. 42-na424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-0111-A
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
	Turner 21
1. oil gas well well other	9. WELL NO.
2. NAME OF OPERATOR Turner Production Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR A. R. Kendrick, Box 516, Aztec, NM 87410	South Blanco-Pictured Cliffs  11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sold SECTION
below.)	21-T26N-R7W: 4 A R R R R R R R R R R R R R R R R R R
AT SURFACE: 2390' FSL 790' FEL Sec. 21	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	Rio Arriba WM
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	30-039-23119
REPORT, OR OTHER DATA	15. TLEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO:  TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE	0201 GR
TEST WATER SHUT-OFF	(NOTEL Report results of multiple completion or zone ) SUR change on Form 9–330.)
FRACTURE TREAT	$\mathcal{A}_{A}}}}}}}}}}$
SHOOT OR ACIDIZE	大声 下海 的复数
REPAIR WELL	(NO PSI Report results of multiple completion or zone )
PULL OR ALTER CASING \( \begin{array}{cccccccccccccccccccccccccccccccccccc	Mr W.
CHANGE ZONES	
ABANDON*	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is d	irectionally drilled, give subsurface locations; and
measured and true vertical depths for all markers and zones pertiner	nt to this work.)*
Spud 12/10/82.	1
Drilled 9 7/8" hole to 98'. Ran 7" 20.0# cas	
cement circulated to surface. (41 cuft Drilled 6 1/4" hole to 2441' RDB. Ran 4 1/2'	1 11 6# cosing to 2/4/1 RDR Comenter
w/172 sx Howco lite plus 55 sx neat cement	Coment did not circulate to
surface. (357 au H.)	<b>報告を表示している。</b>
Ran Cement bond log and GR-CCL. Cement top a	above 1450'.
Perforated Pictured Cliffs 2335' to 2349 & 23	356' to 2362'w/12 0.32' hotes
Acidized w/600 gal 7 1/2% HCl.	
Sand-foam fractured w/40,000# 10-20 sand & 40	0.600 gal 70% foam using 367,000 SCF
Breakdown = 2000 psi. ATP = 1950 psi. AIR =	= 25 BPM. ISIP = 1700 psi.
Ran 1 1/4" tubing to 2317 RDB.	तुं हु हिंदी हैं। भे पूर्व दें
Subsurface Safety Valve: Manu. and Type	<u> </u>
18. I hereby certify that the foregoing is true and correct	10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
SIGNED THE Agent	DATE January 18 7 1983
(This space for Federal or State of	<u> </u>
APPROVED BY TITLE	<sup>2</sup> Agree Land readen
	DATEDATE