

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

5. LEASE DESIGNATION AND SERIAL NO.

SF 079367

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 27-5 Unit

8. FARM OR LEASE NAME

San Juan 27-5 Unit

9. WELL NO.

67A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC. T. R., M., OR BLOCK AND SURVEY OR AREA

Sec. 31, T-27-N, R-5-W

NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

15. DATE SPUDDED

6-20-85

16. DATE T.D. REACHED

6-28-85

17. DATE COMPL. (Ready to prod.)

10-16-85

18. ELEVATIONS (DF, RNB, RT, GE, ETC.)*

6508' GL

19. ELEV. CASINGHEAD

6508'

20. TOTAL DEPTH, MD & TVD

5810'

21. PLUG BACK T.D., MD & TVD

5793'

22. IF MULTIPLE COMPL. HOW MANY*

One

23. INTERVALS DRILLED BY

Rotary

24. CABLE TOOLS

No

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

4816-5703' (Blanco Mesa Verde)

25. WAS DIRECTIONAL SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

Temp Survey
Correlation Gamma-Ray Log; Ind. Gamma-Ray Log; Comp. Density Sidewall NL

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9 5/8"	32.3#	223'	12 1/4"	130 cu ft	
7"	20.0#	3525'	8 3/4"	456 cu ft	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
4 1/2"	3576'	5809'	429 cu ft		2 3/8"	5693'	

30. TUBING RECORD

31. PERFORATION RECORD (Interval, size and number)

5490, 5504, 5533, 5561, 5613, 5632, 5653,
5672, 5703 w/1 SPZ. 2nd stage 5376, 5379,
5382, 5385, 5388, 5391, 5400, 5403, 5406,
5409, 5412, 5422 (Breakdown) 5176, 5201,
5219, 5234, 5239, 5254, 5303, 5439, 5442,

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
5490-5703'	44,000#20/40sand&79,920gals-T wtr
5176-5457'	51,000#20/40sand&130,224gals-T wt
4816-5131'	67,000#20/40sand&145,790gals-T wt

*Continued Perf's Listed on Back Pg. 1

PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
8-14-85		Flowing - Capable of Comm. HC to be tested when connected.				Shut in	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
10-16-85	SI 7 Days	0	→	0	0	0	0
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
SI 432	SI 651	→	No Flow	No Flow	No Flow	0	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Shut in to be Sold

TEST WITNESSED BY
Scott Lindsay

35. LIST OF ATTACHMENTS

Temp Survey

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

Scott Lindsay

TITLE

Drilling Clerk

DATE

10-17-85

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	38. GEOLOGIC MARKERS	
				NAME	TOP MEAS. DEPTH TRUE VERT. DEPTH
Ojo Alamo	2452'	2690'	ss. White cr-grn s.	Ojo Alamo Kirtland Fruitland Pic.Cliffs Chacra Mesa Verde Menefee Point Lookout	2452'
Kirtland	2690'	2935'	Gry sh interbedded w/tight gry fine-grn ss.		2690'
Fruitland	2935'	3183'	Gry carb sh, scattered coals, coals and gry, tight, fine-grn ss.		2935'
Pictured Cliffs	3183'	4097'	Gry, fine-grn tight, varicolored soft ss.		3183'
Chacra	4097'	4810'	Gry fn grn silty, glauconitic sd stone w/drk gry shale		4097'
Mesa Verde	4810'	4933'	Gry, fine-grn, dense sil ss., carb sh & coal		4810'
Menefee	4933'	5367'	Gry, fine-grn s, carb sh & coal		4933'
Point Lookout	5367'	5809'	Gry, very fine sil ss w/frequent sh breaks		5367'
* Continued Perf's:					
5445, 5453, 5457 w/1 SPZ. 3rd stage 4816, 4827, 4847, 4855, 4862, 4880, 4888, 4894, 4901, 4908, 4922, 4932, 5012, 5018, 5030, 5049, 5055, 5077, 5084, 5119, 5131 w/1 SPZ.					