

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

FOR APPROVED
OMB NO. 1004-0137
Expires: December 31, 1991

5. LAND DESIGNATION AND SERIAL NO.

SR-079394

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 27-5 Unit

8. FARM OR LEASE NAME, WELL NO.

San Juan 27-5 U #125E

9. API WELL NO.

30-039-23899

10. FIELD AND POOL, OR WILDCAT

Blanco MV/Basin DK

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

I
Sec. 21, T-27-N, R-5-W

12. COUNTY OR PARISH

Rio Arriba NM

13. STATE

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other

b. TYPE OF COMPLETION: NEW WELL ☐ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. REMV. ☒ Other

2. NAME OF OPERATOR
Meridian Oil Inc

3. ADDRESS AND TELEPHONE NO.
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*
At surface 1560' FSL, 840' FEL

At top prod. interval reported below

At total depth

DHC-1280
14. PERMIT NO. DATE ISSUED

15. DATE SPUDDED 11-28-85 16. DATE T.D. REACHED 12-6-85 17. DATE COMPL. (Ready to prod.) 7-21-96 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 6482 GR 19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD 7713 21. PLUG BACK T.D., MD & TVD 22. IF MULTIPLE COMPL., HOW MANY* 2 23. INTERVALS DRILLED BY ROTARY TOOLS CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 25. WAS DIRECTIONAL SURVEY MADE

4922-5568 Mesaverde
26. TYPES ELECTRIC AND OTHER LOGS RUN GR-CNL, CBL-CCL 27. WAS WELL CORRED

CASING RECORD (Report all strings set in well)				
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD
9 5/8	32.3#	220	12 1/4	177 cu. ft.
7	20#	3566	8 3/4	290 cu. ft.
4 1/2	11.6 & 10.5#	7712	6 1/4	636 cu. ft.

LINER RECORD				TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	BACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)
					1 1/2	7632

31. PERFORATION RECORD (Interval, size and number)		32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.	
4922-4927, 4937-4944, 4965-4985, 5023-5039, 5046-5058, 5434-5444, 5454-5462, 5470-5478, 5478-5492, 5498-5504, 5530-5542, 5560-5568		DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
		4922-5058	689 bbl 30# gel, 155,000# 20/40 sd, 919,000 SCF N2
		5434-5568	616 bbl 30# gel, 120,000# 20/40 sd, 842,000 SCF N2

33. PRODUCTION							
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
7-21-96		Flowing				ST	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
7-21-96					1390 Mesaverde		
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
	ST 830						

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

35. LIST OF ATTACHMENTS To be sold

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED: [Signature] TITLE: Regulatory Administrator

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

AMOOD

AUG 22 1996

ACCEPTED FOR RECORD

FARMINGTON DISTRICT OFFICE

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
Gallup	6440'	7365'	Lt gry to brn calc carb micac glauco very fine gry ss w/irreg. interbed sh
Greenhorn	7365'	7422'	Highly calc gry sh w/thin lmst.
Graneros	7422'	7556'	Dk gry shale, fossil & carb w/pyrite incl.
Dakota	7556'	7712'	Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale

38.

GEOLOGIC MARKERS

NAME	TOP	TRUE VERT. DEPTH
	MEAS. DEPTH	
Gallup	6440'	
Greenhorn	7365'	
Graneros	7422'	
Dakota	7556'	